

## OASIS SET TC

### Use Case Template

**Submitter:** Stephen Green, SystML and Document Engineering Services Ltd

**Use Case:** To guide mapping between a UBL 1.0 and UBL 2.0 Invoice

**Secondary Use Case:** To use SET deliverables to generate CAM templates to support target document

**Goal:** To use SET deliverables to guide mapping between different major versions of a document standard such as UBL and to generate sample transformation stylesheet(s)

**Secondary Goal:** To use SET deliverables to generate CAM templates to support target document

#### Example(s):

From opensource 'freeb-ubl' project

<http://downloads.sourceforge.net/freeb-ubl/freeb-ubl-kit-v1-0.zip>

(see also <http://xml.coverpages.org/freeb-ubl-Announce.html>)

Form this package see:

1. Starting UBL (Subset Conformance Profile) Schema  
see 'freeb-ubl-kit-v1-0/Schemata/UBL1-0/SystML1/'

2. Target UBL (Subset Conformance Profile) Schema and example instance  
see 'freeb-ubl-kit-v1-0/Schemata/UBL2-0/SystML2/'

3. Example Transformation Stylesheet which might be generated – see below and see  
'freeb-ubl-kit-v1-0/VersionToVersion/UBL1SBS1toUBL2/Invoice.xsl'

4. (Secondary Use Case) CAM templates for UBL 2 (SystML2 subset profile) example  
'freeb-ubl-kit-v1-0/CAM/SystML-UBL-2-Invoice-subset-example-template/'

## Transformation Stylesheet

```
<?xml version="1.0" encoding="utf-8"?>
<!--
Created: October 2006 by SystML, http://www.systml.co.uk
-->
<!--
For conversion of UBL 1.0 SBS 1.0 Invoice to UBL 2.0 Invoice.

Limitation: note that codelist values should be checked and
amended for certain codes and coded attributes since there may
be some valid values in UBL 1 which are invalid in UBL 2.0 .
It is suggested that particular attention be given to code values
for '...Quantity/@unitCode'
Care should be taken over indicator values too, noting that 1 and 0
are not allowed in UBL 2.
-->
<!-- Copyright SystML, www.systml.co.uk (2006-2007). All Rights Reserved. -->
<!-- Copyright 2006-2007 The freebXML Foundation
```

Licensed under the freebXML License, Version 2.0 (the "License");  
you may not use this file except in compliance with the License.  
You may obtain a copy of the License at

<http://www.freebXML.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software  
distributed under the License is distributed on an "AS IS" BASIS,  
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.  
See the License for the specific language governing permissions and  
limitations under the License.

```
-->
<xsl:stylesheet xmlns:a="urn:oasis:names:specification:ubl:schema:xsd:Invoice-1.0"
xmlns:cbc="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-1.0"
exclude-result-prefixes="a ca cb xsi" version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
xmlns:ca="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-
1.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" id="SystML-
InvoiceUBL1.0SBS1.0ToUBL2.0-Subset-1.0.10">
    <xsl:output method="xml" indent="yes" encoding="UTF-8" standalone="yes"/>
    <xsl:template match="/">
        <xsl:for-each select="a:Invoice">
            <Invoice
                xmlns:cbc="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-2"
                xmlns:cac="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-
2" xmlns="urn:oasis:names:specification:ubl:schema:xsd:Invoice-2">
                <cbc:UBLVersionID>2.0</cbc:UBLVersionID>
                <xsl:for-each select="a:ID">
                    <cbc:ID>
                        <xsl:if test="@identificationSchemeID">
```

```

<xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeName">
<xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeAgencyID">
<xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyName">
<xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeVersionID">
<xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeDataURI">
<xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeURI">
<xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of select="."/>
</cbc:ID>
</xsl:for-each>
<xsl:for-each select="cb:CopyIndicator">
<cbc:CopyIndicator>
<xsl:value-of select="."/>
</cbc:CopyIndicator>
</xsl:for-each>
<xsl:for-each select="a:GUID">
<cbc:UUID>
<xsl:if test="@identificationSchemeID">
<xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeName">
<xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
</xsl:if>
```

```

<xsl:if test="@identificationSchemeAgencyID">
    <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
    </xsl:if>
    <xsl:if
test="@identificationSchemeAgencyName">
        <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
        </xsl:if>
        <xsl:if test="@identificationSchemeVersionID">
            <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
            </xsl:if>
            <xsl:if test="@identificationSchemeDataURI">
                <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeURI">
                    <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
                    </xsl:if>
                    <xsl:value-of select=". "/>
                    </cbc:UUID>
                </xsl:for-each>
                <xsl:for-each select="cb:IssueDate">
                    <cbc:IssueDate>
                        <xsl:value-of select=". "/>
                    </cbc:IssueDate>
                </xsl:for-each>
                <xsl:for-each select="a:InvoiceTypeCode">
                    <cbc:InvoiceTypeCode>
                        <xsl:if test="@codeListID">
                            <xsl:attribute name="listID"><xsl:value-
of select="@codeListID"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if test="@codeListAgencyID">
                            <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>
                            </xsl:if>
                            <xsl:if test="@codeListAgencyName">
                                <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>
                                </xsl:if>
                                <xsl:if test="@codeListName">
                                    <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>
                                </xsl:if>
                            </xsl:if>
                        </xsl:if>
                    </cbc:InvoiceTypeCode>
                </xsl:for-each>
            </xsl:if>
        </xsl:if>
    </xsl:if>
</xsl:if>

```

```

        </xsl:if>
        <xsl:if test="@codeListVersionID">
            <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>
        </xsl:if>
        <xsl:if test="@name">
            <xsl:attribute name="name"><xsl:value-
of select="@name"/></xsl:attribute>
        </xsl:if>
        <xsl:if test="@languageID">
            <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
        </xsl:if>
        <xsl:if test="@codeListURI">
            <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>
        </xsl:if>
        <xsl:if test="@codeListSchemeURI">
            <xsl:attribute
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>
        </xsl:if>
        <xsl:value-of select=". "/>
            <cbc:InvoiceTypeCode>
        </xsl:for-each>
        <xsl:for-each select="cb:Note">
            <cbc:Note>
                <xsl:if test="@languageID">
                    <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                </xsl:if>
                <xsl:value-of select=". "/>
                    <cbc:Note>
                </xsl:for-each>
                <xsl:for-each select="a:TaxPointDate">
                    <cbc:TaxPointDate>
                        <xsl:value-of select=". "/>
                    </cbc:TaxPointDate>
                </xsl:for-each>
                <xsl:for-each select="ca:OrderReference">
                    <cac:OrderReference>
                        <xsl:for-each select="ca:BuyersID">
                            <cbc:ID>
                                <xsl:if
test="@identificationSchemeID">
                                    <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
                                </xsl:if>
                                <xsl:if
test="@identificationSchemeName">

```

```

        <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyID">
        <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyName">
        <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeVersionID">
        <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeDataURI">
        <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeURI">
        <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
        </xsl:if>
        <xsl:value-of select="."/>
        </cbc:ID>
</xsl:for-each>
<xsl:for-each select="ca:SellersID">
        <cbc:SalesOrderID>
        <xsl:if
test="@identificationSchemeID">
        <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeName">
        <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyID">

```

```

<xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyName">
<xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeVersionID">
<xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeDataURI">
<xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeURI">
<xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of select="."/>
</cbc:SalesOrderID>
</xsl:for-each>
<xsl:for-each select="ca:GUID">
<cbc:UUID>
<xsl:if
test="@identificationSchemeID">
<xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeName">
<xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyID">
<xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyName">

```

```

<xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeVersionID">
<xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeDataURI">
<xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeURI">
<xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:UUID>
</xsl:for-each>
<xsl:for-each select="cb:IssueDate">
<cbc:IssueDate>
<xsl:value-of select=". "/>
</cbc:IssueDate>
</xsl:for-each>
</cac:OrderReference>
</xsl:for-each>
<xsl:for-each select="ca:SellerParty">
<cac:AccountingSupplierParty>
<xsl:for-each
select="ca:BuyerAssignedAccountID">
<cbc:CustomerAssignedAccountID>
<xsl:if
test="@identificationSchemeID">
<xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeName">
<xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyID">

```

```

<xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyName">
<xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeVersionID">
<xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeDataURI">
<xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeURI">
<xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of select="."/>
</cbc:CustomerAssignedAccountID>
</xsl:for-each>
<xsl:for-each select="ca:Party">
<cac:Party>
<xsl:for-each
select="ca:PartyIdentification">
<cac:PartyIdentification>
<xsl:for-each
select="ca:ID">
<cbc:ID>
<xsl:if test="@identificationSchemeID">
<xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeName">
<xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

```

```

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">
  <xsl:attribute name="schemeAgencyID"><xsl:value-of
  select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">
  <xsl:attribute name="schemeAgencyName"><xsl:value-of
  select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeVersionID">
  <xsl:attribute name="schemeVersionID"><xsl:value-of
  select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeDataURI">
  <xsl:attribute name="schemeDataURI"><xsl:value-of
  select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeURI">
  <xsl:attribute name="schemeURI"><xsl:value-of
  select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>

<xsl:value-of select=". "/>
  </cbc:ID>
  </xsl:for-each>
  </cac:PartyIdentification>
  </xsl:for-each>
  <xsl:for-each
select="ca:PartyName">
  <cac:PartyName>
    <xsl:for-each
select="cb:Name">
      <cbc:Name>

```

```

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select=". "/>

    </cbc:Name>
        </xsl:for-each>
    </cac:PartyName>
        </xsl:for-each>
    <xsl:for-each

select="ca:Address">
        <cac:PostalAddress>
            <xsl:for-each

select="cb:ID">
            <cbc:ID>

        <xsl:if test="@identificationSchemeID">

            <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@identificationSchemeName">

                <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

                </xsl:if>

            <xsl:if test="@identificationSchemeAgencyID">

                <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

                </xsl:if>

            <xsl:if test="@identificationSchemeAgencyName">

                <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

                </xsl:if>

            <xsl:if test="@identificationSchemeVersionID">

```

```

<xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

<xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

<xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>                                </cbc:ID>
</xsl:for-each>
<xsl:for-each
select="cb:Postbox">

<cbc:Postbox>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:Postbox>                                         </xsl:for-each>
<xsl:for-each
select="cb:StreetName">

<cbc:StreetName>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

```

```
<xsl:value-of select=". "/>

</cbc:StreetName>
</xsl:for-each>
<xsl:for-each

select="cb:BuildingName">

<cbc:BuildingName>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:BuildingName>
</xsl:for-each>
<xsl:for-each

select="cb:BuildingNumber">

<cbc:BuildingNumber>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:BuildingNumber>
</xsl:for-each>
<xsl:for-each

select="cb:Department">

<cbc:Department>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
```

```
</cbc:Department>
</xsl:for-each>
<xsl:for-each
select="cb:CityName">

<cbc:CityName>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:CityName>
</xsl:for-each>
<xsl:for-each

select="cb:PostalZone">

<cbc:PostalZone>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:PostalZone>
</xsl:for-each>
<xsl:for-each

select="cb:CountrySubentity">

<cbc:CountrySubentity>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:CountrySubentity>
```

```

        </xsl:for-each>
        <xsl:for-each

select="ca:AddressLine">

    <cac:AddressLine>

        <xsl:for-each select="cb:Line">

            <cbc:Line>

                <xsl:if test="@languageID">

                    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

                </xsl:if>

                <xsl:value-of select=". "/>

            </cbc:Line>

        </xsl:for-each>

    </cac:AddressLine>

        </xsl:for-each>
        <xsl:for-each

select="ca:Country">

    <cac:Country>

        <xsl:for-each select="ca:IdentificationCode">

            <cbc:IdentificationCode>

                <xsl:if test="@codeListID">

                    <xsl:attribute name="listID"><xsl:value-of
select="@codeListID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListAgencyID">

                    <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListAgencyName">

```

```
        <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListName">

        <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListVersionID">

        <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@name">

        <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@languageID">

        <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListURI">

        <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListSchemeURI">

        <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select="."/>

</cbc:IdentificationCode>
```

```

</xsl:for-each>

<xsl:for-each select="cb:Name">
  <cbc:Name>
    <xsl:if test="@languageID">
      <xsl:attribute name="languageID"><xsl:value-of
      select="@languageID"/></xsl:attribute>
    </xsl:if>
    <xsl:value-of select=". "/>
  </cbc:Name>
</xsl:for-each>

</cac:Country>
  </xsl:for-each>
  </cac:PostalAddress>
</xsl:for-each>
<xsl:for-each
select="ca:PartyTaxScheme">
  <cac:PartyTaxScheme>
    <xsl:for-each
select="cb:RegistrationName">
      <cbc:RegistrationName>
        <xsl:if test="@languageID">
          <xsl:attribute name="languageID"><xsl:value-of
          select="@languageID"/></xsl:attribute>
        </xsl:if>
        <xsl:value-of select=". "/>
      </cbc:RegistrationName>
    </xsl:for-each>
    <xsl:for-each
select="ca:CompanyID">
      <cbc:CompanyID>
        <xsl:if test="@identificationSchemeID">

```

```
<xsl:attribute name="schemeID"><xsl:value-of  
select="@identificationSchemeID"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@identificationSchemeName">  
  
    <xsl:attribute name="schemeName"><xsl:value-of  
select="@identificationSchemeName"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@identificationSchemeAgencyID">  
  
    <xsl:attribute name="schemeAgencyID"><xsl:value-of  
select="@identificationSchemeAgencyID"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@identificationSchemeAgencyName">  
  
    <xsl:attribute name="schemeAgencyName"><xsl:value-of  
select="@identificationSchemeAgencyName"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@identificationSchemeVersionID">  
  
    <xsl:attribute name="schemeVersionID"><xsl:value-of  
select="@identificationSchemeVersionID"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@identificationSchemeDataURI">  
  
    <xsl:attribute name="schemeDataURI"><xsl:value-of  
select="@identificationSchemeDataURI"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@identificationSchemeURI">  
  
    <xsl:attribute name="schemeURI"><xsl:value-of  
select="@identificationSchemeURI"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:value-of select=". />  
  
</cbc:CompanyID>
```

```

        </xsl:for-each>
        <xsl:for-each

select="cb:ExemptionReason">

    <cbc:ExemptionReason>

        <xsl:if test="@languageID">

            <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

        </xsl:if>

        <xsl:value-of select=". "/>

    </cbc:ExemptionReason>
        </xsl:for-each>
        <xsl:for-each

select="ca:TaxScheme">

    <cac:TaxScheme>

        <xsl:for-each select="ca:ID">

            <cbc:ID>

                <xsl:if test="@identificationSchemeID">

                    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@identificationSchemeName">

                    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@identificationSchemeAgencyID">

                    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@identificationSchemeAgencyName">

```

```
        <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeVersionID">

        <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeDataURI">

        <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeURI">

        <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select="."/>

</cbc:ID>

</xsl:for-each>

<xsl:for-each select="ca:TaxTypeCode">

<cbc:TaxTypeCode>

    <xsl:if test="@codeListID">

        <xsl:attribute name="listID"><xsl:value-of
select="@codeListID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListAgencyID">

        <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>

    </xsl:if>
```

```
<xsl:if test="@codeListAgencyName">

    <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListName">

    <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListVersionID">

    <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@name">

    <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

</xsl:if>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListURI">

    <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListSchemeURI">

    <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

</xsl:if>
```

```

<xsl:value-of select=". "/>

</cbc:TaxTypeCode>

</xsl:for-each>

</cac:TaxScheme>
                                </xsl:for-each>
                                </cac:PartyTaxScheme>
                                </xsl:for-each>
                                <xsl:for-each select="ca>Contact">
                                    <cac>Contact>
                                    <xsl:for-each
select="cb:ID">
                                        <cbc:ID>

<xsl:if test="@identificationSchemeID">
    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeName">
    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">
    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">
    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeVersionID">
    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

```

```

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

  <xsl:attribute name="schemeDataURI"><xsl:value-of
  select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

  <xsl:attribute name="schemeURI"><xsl:value-of
  select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
          </cbc:ID>
</xsl:for-each>
<xsl:for-each

select="cb:Name">
          <cbc:Name>

<xsl:if test="@languageID">

  <xsl:attribute name="languageID"><xsl:value-of
  select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
          </cbc:Name>
          </xsl:for-each>
<xsl:for-each

select="cb:Telephone">
          <cbc:Telephone>

<xsl:if test="@languageID">

  <xsl:attribute name="languageID"><xsl:value-of
  select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
          </cbc:Telephone>

```

```

select="cb:Telefax">
<cbc:Telefax>
<xsl:if test="@languageID">
  <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:Telefax>

```

</xsl:for-each>  
<xsl:for-each>

```

select="cb:ElectronicMail">
<cbc:ElectronicMail>
<xsl:if test="@languageID">
  <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:ElectronicMail>

```

</xsl:for-each>  
</cac:Contact>  
</xsl:for-each>  
</cac:Party>  
</xsl:for-each>  
</cac:AccountingSupplierParty>  
</xsl:for-each>  
<xsl:for-each select="ca:BuyerParty">
 <cac:AccountingCustomerParty>
 <xsl:for-each>
 <cbc:CustomerAssignedAccountID>
 <xsl:if
test="@identificationSchemeID">
 <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
 </xsl:if>

```

<xsl:if
test="@identificationSchemeName">
    <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyID">
    <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyName">
    <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeVersionID">
    <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeDataURI">
    <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeURI">
    <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
        </xsl:if>
        <xsl:value-of select=". "/>
        <cbc:CustomerAssignedAccountID>
            </xsl:for-each>
            <xsl:for-each
select="ca:SellerAssignedAccountID">
                <cbc:SupplierAssignedAccountID>
                    <xsl:if
test="@identificationSchemeID">
    <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeName">
    <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
        </xsl:if>

```

```

<xsl:if
test="@identificationSchemeAgencyID">
    <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
    </xsl:if>
    <xsl:if
test="@identificationSchemeAgencyName">
    <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
    </xsl:if>
    <xsl:if
test="@identificationSchemeVersionID">
    <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
    </xsl:if>
    <xsl:if
test="@identificationSchemeDataURI">
    <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
    </xsl:if>
    <xsl:if
test="@identificationSchemeURI">
    <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
    </xsl:if>
    <xsl:value-of select="."/>
    </cbc:SupplierAssignedAccountID>
    </xsl:for-each>
    <xsl:for-each select="ca:Party">
        <cac:Party>
        <xsl:for-each
select="ca:PartyIdentification">
            <cac:PartyIdentification>
            <xsl:for-each
select="ca:ID">
                <cbc:ID>
<xsl:if test="@identificationSchemeID">
    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if test="@identificationSchemeName">

```

```

<xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

  <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">

  <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">

  <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

  <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

  <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
                                </cbc:ID>
                                </xsl:for-each>
                                </cac:PartyIdentification>
                                </xsl:for-each>
                                <xsl:for-each
select="ca:PartyName">
                                <cac:PartyName>
                                    <xsl:for-each
select="cb:Name">

```

```

<cbc:Name>

<xsl:if test="@languageID">
  <xsl:attribute name="languageID"><xsl:value-of
  select="@languageID"/></xsl:attribute>

  </xsl:if>

  <xsl:value-of select=". "/>

</cbc:Name>
  </xsl:for-each>
  </cac:PartyName>
</xsl:for-each>
<xsl:for-each
select="ca:Address">
  <cac:PostalAddress>
    <xsl:for-each
select="cb:ID">
      <cbc:ID>

      <xsl:if test="@identificationSchemeID">
        <xsl:attribute name="schemeID"><xsl:value-of
        select="@identificationSchemeID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@identificationSchemeName">
          <xsl:attribute name="schemeName"><xsl:value-of
          select="@identificationSchemeName"/></xsl:attribute>

          </xsl:if>

        <xsl:if test="@identificationSchemeAgencyID">
          <xsl:attribute name="schemeAgencyID"><xsl:value-of
          select="@identificationSchemeAgencyID"/></xsl:attribute>

          </xsl:if>

        <xsl:if test="@identificationSchemeAgencyName">
          <xsl:attribute name="schemeAgencyName"><xsl:value-of
          select="@identificationSchemeAgencyName"/></xsl:attribute>

          </xsl:if>

```

```

<xsl:if test="@identificationSchemeVersionID">

  <xsl:attribute name="schemeVersionID"><xsl:value-of
  select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

  <xsl:attribute name="schemeDataURI"><xsl:value-of
  select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

  <xsl:attribute name="schemeURI"><xsl:value-of
  select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>                                </cbc:ID>
select="cb:Postbox">                                         </xsl:for-each>
<xsl:for-each

<cfc:Postbox>

<xsl:if test="@languageID">

  <xsl:attribute name="languageID"><xsl:value-of
  select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cfc:Postbox>                                         </xsl:for-each>
<xsl:for-each

select="cb:StreetName">

<cfc:StreetName>

<xsl:if test="@languageID">

  <xsl:attribute name="languageID"><xsl:value-of
  select="@languageID"/></xsl:attribute>

```

```
</xsl:if>

<xsl:value-of select=". "/>

</cbc:StreetName>
select="cb:BuildingName">
<cbc:BuildingName>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:BuildingName>
select="cb:BuildingNumber">
<cbc:BuildingNumber>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:BuildingNumber>
select="cb:Department">
<cbc:Department>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
```

```
<xsl:value-of select=". "/>

</cbc:Department>
</xsl:for-each>
<xsl:for-each

select="cb:CityName">

<cbc:CityName>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:CityName>
</xsl:for-each>
<xsl:for-each

select="cb:PostalZone">

<cbc:PostalZone>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:PostalZone>
</xsl:for-each>
<xsl:for-each

select="cb:CountrySubentity">

<cbc:CountrySubentity>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
```

```

</cbc:CountrySubentity>
</xsl:for-each>
<xsl:for-each
select="ca:AddressLine">

<cac:AddressLine>
<xsl:for-each select="cb:Line">
<cbc:Line>
<xsl:if test="@languageID">
<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of select=". "/>
</cbc:Line>
</xsl:for-each>
</cac:AddressLine>
</xsl:for-each>
<xsl:for-each
select="ca:Country">

<cac:Country>
<xsl:for-each select="ca:IdentificationCode">
<cbc:IdentificationCode>
<xsl:if test="@codeListID">
<xsl:attribute name="listID"><xsl:value-of
select="@codeListID"/></xsl:attribute>
</xsl:if>
<xsl:if test="@codeListAgencyID">
<xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>
</xsl:if>

```

```
<xsl:if test="@codeListAgencyName">

    <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListName">

    <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListVersionID">

    <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@name">

    <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

</xsl:if>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListURI">

    <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListSchemeURI">

    <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

</xsl:if>
```

```

<xsl:value-of select=". "/>

</cbc:IdentificationCode>

</xsl:for-each>

<xsl:for-each select="cb:Name">

<cbc:Name>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:Name>

</xsl:for-each>

</cac:Country>
    </xsl:for-each>
    </cac:PostalAddress>
</xsl:for-each>
<xsl:for-each
select="ca:PartyTaxScheme">
    <cac:PartyTaxScheme>
        <xsl:for-each
select="cb:RegistrationName">

<cbc:RegistrationName>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:RegistrationName>
    </xsl:for-each>
<xsl:for-each
select="ca:CompanyID">

```

```
<cbc:CompanyID>

<xsl:if test="@identificationSchemeID">

    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeName">

    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">

    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">

    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

    <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>
```

```

</xsl:if>

<xsl:value-of select=". "/>

</cbc:CompanyID>
</xsl:for-each>
<xsl:for-each
select="cb:ExemptionReason">

<cbc:ExemptionReason>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:ExemptionReason>
</xsl:for-each>
<xsl:for-each
select="ca:TaxScheme">

<cac:TaxScheme>

<xsl:for-each select="ca:ID">

<cbc:ID>

<xsl:if test="@identificationSchemeID">

<xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeName">

<xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

<xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

```

```
</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">
    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">
    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">
    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">
    <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select="."/>

</cbc:ID>

</xsl:for-each>

<xsl:for-each select="ca:TaxTypeCode">
    <cbc:TaxTypeCode>
        <xsl:if test="@codeListID">
            <xsl:attribute name="listID"><xsl:value-of
select="@codeListID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListAgencyID">
```

```
        <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListAgencyName">

        <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListName">

        <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListVersionID">

        <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@name">

        <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@languageID">

        <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListURI">

        <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListSchemeURI">
```

```

        <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

        </xsl:if>

        <xsl:value-of select=". "/>

</cbc:TaxTypeCode>

</xsl:for-each>

</cac:TaxScheme>
                </xsl:for-each>
                </cac:PartyTaxScheme>
            </xsl:for-each>
            <xsl:for-each select="ca>Contact">
                <cac>Contact>
                    <xsl:for-each
select="cb>ID">
                        <cbc:ID>
<xsl:if test="@identificationSchemeID">

        <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@identificationSchemeName">

        <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@identificationSchemeAgencyID">

        <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@identificationSchemeAgencyName">

        <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@identificationSchemeVersionID">

```

```

<xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

<xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

<xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
</cbc:ID>
</xsl:for-each>
<xsl:for-each

select="cb:Name">
<cbc:Name>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>
</cbc:Name>
</xsl:for-each>
<xsl:for-each

select="cb:Telephone">
<cbc:Telephone>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

```

```

<xsl:value-of select=". "/>

</cbc:Telephone>
</xsl:for-each>
<xsl:for-each

select="cb:Telefax">

<cbc:Telefax>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:Telefax>
</xsl:for-each>
<xsl:for-each

select="cb:ElectronicMail">

<cbc:ElectronicMail>

<xsl:if test="@languageID">

<xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:ElectronicMail>
</xsl:for-each>
</cac:Contact>
</xsl:for-each>
</cac:Party>
</xsl:for-each>
</cac:AccountingCustomerParty>
</xsl:for-each>
<xsl:for-each select="ca:Delivery">
<cac:Delivery>
<xsl:for-each

select="cb:ActualDeliveryDateTime">
<cbc:ActualDeliveryDate>
<xsl:value-of select="substring-
before(.,'T')"/>

```

```

                </cbc:ActualDeliveryDate>
            </xsl:for-each>
            <xsl:for-each
select="cb:ActualDeliveryDateTime">
                <cbc:ActualDeliveryTime>
                    <xsl:value-of select="substring-
after(.,'T')"/>
                <cbc:ActualDeliveryTime>
            </xsl:for-each>
            <xsl:for-each select="ca:DeliveryAddress">
                <cac:DeliveryAddress>
                    <xsl:for-each select="cb:ID">
                        <cbc:ID>
                            <xsl:if
test="@identificationSchemeID">
                            <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if
test="@identificationSchemeName">
                            <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if
test="@identificationSchemeAgencyID">
                            <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if
test="@identificationSchemeAgencyName">
                            <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if
test="@identificationSchemeVersionID">
                            <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if
test="@identificationSchemeDataURI">
                            <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if
test="@identificationSchemeURI">

```

```

<xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>
</cbc:ID>
</xsl:for-each>
<xsl:for-each
select="cb:Postbox">
<cbc:Postbox>
<xsl:if
test="@languageID">
<xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>
</cbc:Postbox>
</xsl:for-each>
<xsl:for-each
select="cb:StreetName">
<cbc:StreetName>
<xsl:if
test="@languageID">
<xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>
</cbc:StreetName>
</xsl:for-each>
<xsl:for-each
select="cb:BuildingName">
<cbc:BuildingName>
<xsl:if
test="@languageID">
<xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>
</cbc:BuildingName>
</xsl:for-each>
<xsl:for-each
select="cb:BuildingNumber">
<cbc:BuildingNumber>
<xsl:if
test="@languageID">
<xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>

```

```

        </xsl:if>
        <xsl:value-of

select=". "/>
                </cbc:BuildingNumber>
            </xsl:for-each>
            <xsl:for-each

select="cb:Department">
                <cbc:Department>
                    <xsl:if

test="@languageID">
                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:value-of

select=". "/>
                </cbc:Department>
            </xsl:for-each>
            <xsl:for-each

select="cb:CityName">
                <cbc:CityName>
                    <xsl:if

test="@languageID">
                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:value-of

select=". "/>
                </cbc:CityName>
            </xsl:for-each>
            <xsl:for-each

select="cb:PostalZone">
                <cbc:PostalZone>
                    <xsl:if

test="@languageID">
                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:value-of

select=". "/>
                </cbc:PostalZone>
            </xsl:for-each>
            <xsl:for-each

select="cb:CountrySubentity">
                <cbc:CountrySubentity>
                    <xsl:if

test="@languageID">
                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                    </xsl:if>

```

```

        <xsl:value-of
select=". "/>
                </cbc:CountrySubentity>
            </xsl:for-each>
            <xsl:for-each

select="ca:AddressLine">
                <cac:AddressLine>
                    <xsl:for-each

select="cb:Line">
                <cbc:Line>

<xsl:if test="@languageID">
    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
</xsl:if>

<xsl:value-of select=". "/>
                </cbc:Line>
            </xsl:for-each>
            </cac:AddressLine>
        </xsl:for-each>
        <xsl:for-each

select="ca:Country">
                <cac:Country>
                    <xsl:for-each

select="ca:IdentificationCode">
                <cbc:IdentificationCode>

                <xsl:if test="@codeListID">
                    <xsl:attribute name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@codeListAgencyID">
                    <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@codeListAgencyName">
                    <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>
                </xsl:if>

```

```

<xsl:if test="@codeListName">

    <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListVersionID">

    <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@name">

    <xsl:attribute name="name"><xsl:value-of select="@name"/></xsl:attribute>

</xsl:if>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListURI">

    <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListSchemeURI">

    <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:IdentificationCode>
</xsl:for-each>
<xsl:for-each
select="cb:Name">
    <cbc:Name>

```

```

<xsl:if test="@languageID">
  <xsl:attribute name="languageID"><xsl:value-of
  select="@languageID"/></xsl:attribute>

  </xsl:if>

  <xsl:value-of select=".."/>

  </cbc:Name>
    </xsl:for-each>
    </cac:Country>
      </xsl:for-each>
      </cac:DeliveryAddress>
        </xsl:for-each>
        <xsl:for-each
select="cb:RequestedDeliveryDateTime">
  <cac:RequestedDeliveryPeriod>
    <cbc:StartDate>
      <xsl:value-of
      select="substring-before(.,'T')"/>
      </cbc:StartDate>
      <cbc:StartTime>
        <xsl:value-of
        select="substring-after(.,'T')"/>
        </cbc:StartTime>
        <cbc:EndDate>
          <xsl:value-of
          select="substring-before(.,'T')"/>
          </cbc:EndDate>
          <cbc:EndTime>
            <xsl:value-of
            select="substring-after(.,'T')"/>
            </cbc:EndTime>
            </cac:RequestedDeliveryPeriod>
          </xsl:for-each>
        </cac:Delivery>
      </xsl:for-each>
      <xsl:for-each select="ca:PaymentMeans">
        <cac:PaymentMeans>
          <xsl:for-each select="ca:PaymentMeansCode">
            <cbc:PaymentMeansCode>
              <xsl:if test="@codeListID">
                <xsl:attribute
name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>
                </xsl:if>
              <xsl:if
test="@codeListAgencyID">

```

```

        <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>
            </xsl:if>
            <xsl:if
test="@codeListAgencyName">
                <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if test="@codeListName">
                        <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>
                            </xsl:if>
                            <xsl:if
test="@codeListVersionID">
                                <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>
                                    </xsl:if>
                                    <xsl:if test="@name">
                                        <xsl:attribute
name="name"><xsl:value-of select="@name"/></xsl:attribute>
                                            </xsl:if>
                                            <xsl:if test="@languageID">
                                                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                                                    </xsl:if>
                                                    <xsl:if test="@codeListURI">
                                                        <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>
                                                            </xsl:if>
                                                            <xsl:if
test="@codeListSchemeURI">
                                                                <xsl:attribute
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>
                                                                    </xsl:if>
                                                                    <xsl:value-of select=". "/>
                                                                    </cbc:PaymentMeansCode>
                                                                </xsl:for-each>
                                                                <xsl:for-each select="cb:DuePaymentDate">
                                                                    <cbc:PaymentDueDate>
                                                                        <xsl:value-of select=". "/>
                                                                    </cbc:PaymentDueDate>
                                                                </xsl:for-each>
                                                                <xsl:for-each
select="ca:PayeeFinancialAccount">
                                                                    <cac:PayeeFinancialAccount>
                                                                        <xsl:for-each select="ca:ID">
                                                                            <cbc:ID>
                                                                                <xsl:if
test="@identificationSchemeID">

```

```

<xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeName">
<xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyID">
<xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeAgencyName">
<xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeVersionID">
<xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeDataURI">
<xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@identificationSchemeURI">
<xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>
</cbc:ID>
</xsl:for-each>
<xsl:for-each select="cb:Name">
<cbc:Name>
<xsl:if
test="@languageID">
<xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>

```

```

                </cbc:Name>
            </xsl:for-each>
            <xsl:for-each
select="ca:AccountTypeCode">
                <cbc:AccountTypeCode>
                    <xsl:if
test="@codeListID">
                        <xsl:attribute
name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListAgencyID">
                        <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListAgencyName">
                        <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListName">
                        <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListVersionID">
                        <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@name">
                        <xsl:attribute
name="name"><xsl:value-of select="@name"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@languageID">
                        <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListURI">
                        <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListSchemeURI">
                        <xsl:attribute
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>
                    </xsl:if>

```

```

        <xsl:value-of
select=". "/>
                </cbc:AccountTypeCode>
            </xsl:for-each>
            <xsl:for-each
select="ca:CurrencyCode">
                <cbc:CurrencyCode>
                <xsl:if
test="@codeListID">
                    <xsl:attribute
name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListAgencyID">
                    <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListAgencyName">
                    <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListName">
                    <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListVersionID">
                    <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@name">
                    <xsl:attribute
name="name"><xsl:value-of select="@name"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@languageID">
                    <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListURI">
                    <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListSchemeURI">

```

```
        <xsl:attribute  
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>  
        </xsl:if>  
        <xsl:value-of  
select=". "/>  
            </cbc:CurrencyCode>  
        </xsl:for-each>  
        <xsl:for-each  
select="ca:FinancialInstitutionBranch">  
            <cac:FinancialInstitutionBranch>  
                <xsl:for-each  
select="ca:ID">  
                    <cbc:ID>  
                        <xsl:if test="@identificationSchemeID">  
                            <xsl:attribute name="schemeID"><xsl:value-of  
select="@identificationSchemeID"/></xsl:attribute>  
                        </xsl:if>  
                        <xsl:if test="@identificationSchemeName">  
                            <xsl:attribute name="schemeName"><xsl:value-of  
select="@identificationSchemeName"/></xsl:attribute>  
                        </xsl:if>  
                        <xsl:if test="@identificationSchemeAgencyID">  
                            <xsl:attribute name="schemeAgencyID"><xsl:value-of  
select="@identificationSchemeAgencyID"/></xsl:attribute>  
                        </xsl:if>  
                        <xsl:if test="@identificationSchemeAgencyName">  
                            <xsl:attribute name="schemeAgencyName"><xsl:value-of  
select="@identificationSchemeAgencyName"/></xsl:attribute>  
                        </xsl:if>  
                        <xsl:if test="@identificationSchemeVersionID">  
                            <xsl:attribute name="schemeVersionID"><xsl:value-of  
select="@identificationSchemeVersionID"/></xsl:attribute>  
                        </xsl:if>
```

```

<xsl:if test="@identificationSchemeDataURI">

    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

    <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>                                </cbc:ID>
select="cb:Name">                                         </xsl:for-each>
                                                        <xsl:for-each
select="cbc:Name">                                         <cbc:Name>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>                                </xsl:for-each>
</cbc:Name>                                         <xsl:for-each
select="ca:FinancialInstitution">

    <cac:FinancialInstitution>

    <xsl:for-each select="ca:ID">

        <cbc:ID>

            <xsl:if test="@identificationSchemeID">

                <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@identificationSchemeName">

```

```

        <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

        <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">

        <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">

        <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

        <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

        <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select="."/>

</cbc:ID>

</xsl:for-each>

<xsl:for-each select="cb:Name">

<cbc:Name>

```

```

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select=". "/>

</cbc:Name>

</xsl:for-each>

<xsl:for-each select="ca:Address">

<cac:Address>

    <xsl:for-each select="cb:ID">

        <cbc:ID>

            <xsl:if test="@identificationSchemeID">

                <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@identificationSchemeName">

                <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@identificationSchemeAgencyID">

                <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@identificationSchemeAgencyName">

                <xsl:attribute name="schemeAgencyName"><xsl:value-
of select="@identificationSchemeAgencyName"/></xsl:attribute>

            </xsl:if>

```

```

<xsl:if test="@identificationSchemeVersionID">

    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

    <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:ID>

</xsl:for-each>

<xsl:for-each select="cb:Postbox">

    <cbc:Postbox>

        <xsl:if test="@languageID">

            <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:Postbox>

</xsl:for-each>

<xsl:for-each select="cb:StreetName">

    <cbc:StreetName>

        <xsl:if test="@languageID">

```

```

        <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

        </xsl:if>

        <xsl:value-of select=". "/>

    </cbc:StreetName>

</xsl:for-each>

<xsl:for-each select="cb:BuildingName">

    <cbc:BuildingName>

        <xsl:if test="@languageID">

            <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

            </xsl:if>

            <xsl:value-of select=". "/>

        </cbc:BuildingName>

    </xsl:for-each>

    <xsl:for-each select="cb:BuildingNumber">

        <cbc:BuildingNumber>

            <xsl:if test="@languageID">

                <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

                </xsl:if>

                <xsl:value-of select=". "/>

            </cbc:BuildingNumber>

        </xsl:for-each>

        <xsl:for-each select="cb:Department">

            <cbc:Department>

```

```

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:Department>

</xsl:for-each>

<xsl:for-each select="cb:CityName">

<cbc:CityName>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:CityName>

</xsl:for-each>

<xsl:for-each select="cb:PostalZone">

<cbc:PostalZone>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:PostalZone>

</xsl:for-each>

<xsl:for-each select="cb:CountrySubentity">

```

```
<cbc:CountrySubentity>

    <xsl:if test="@languageID">
        <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

        </xsl:if>
        <xsl:value-of select=". "/>
    </cbc:CountrySubentity>

</xsl:for-each>

<xsl:for-each select="ca:AddressLine">

    <cac:AddressLine>
        <xsl:for-each select="cb:Line">
            <cbc:Line>
                <xsl:if test="@languageID">
                    <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>

                    </xsl:if>
                    <xsl:value-of select=". "/>
                </cbc:Line>
            </xsl:for-each>
        </cac:AddressLine>
    </xsl:for-each>

    <cbc:Country>
        <xsl:for-each select="ca:IdentificationCode">
            <cbc:IdentificationCode>
                <xsl:if test="@codeListID">
```

```

        <xsl:attribute name="listID"><xsl:value-
of select="@codeListID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListAgencyID">

                        <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListAgencyName">

                        <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListName">

                        <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListVersionID">

                        <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@name">

                        <xsl:attribute name="name"><xsl:value-
of select="@name"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@languageID">

                        <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListURI">

```

```

        <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@codeListSchemeURI">

            <xsl:attribute
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>

            </xsl:if>

            <xsl:value-of select="."/>

        </cbc:IdentificationCode>

    </xsl:for-each>

    <xsl:for-each select="cb:Name">

        <cbc:Name>

            <xsl:if test="@languageID">

                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>

                </xsl:if>

                <xsl:value-of select="."/>

            </cbc:Name>

        </xsl:for-each>

    </cac:Country>

</xsl:for-each>

</cac:Address>

</xsl:for-each>

</cac:FinancialInstitution>
select="ca:Address">
<cac:Address>
        </xsl:for-each>
        <xsl:for-each>

```

```

<xsl:for-each select="cb:ID">

  <cbc:ID>

    <xsl:if test="@identificationSchemeID">

      <xsl:attribute name="schemeID"><xsl:value-of
      select="@identificationSchemeID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeName">

      <xsl:attribute name="schemeName"><xsl:value-of
      select="@identificationSchemeName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeAgencyID">

      <xsl:attribute name="schemeAgencyID"><xsl:value-of
      select="@identificationSchemeAgencyID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeAgencyName">

      <xsl:attribute name="schemeAgencyName"><xsl:value-of
      select="@identificationSchemeAgencyName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeVersionID">

      <xsl:attribute name="schemeVersionID"><xsl:value-of
      select="@identificationSchemeVersionID"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeDataURI">

      <xsl:attribute name="schemeDataURI"><xsl:value-of
      select="@identificationSchemeDataURI"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@identificationSchemeURI">

```

```
    <xsl:attribute name="schemeURI"><xsl:value-of  
select="@identificationSchemeURI"/></xsl:attribute>  
  
    </xsl:if>  
  
    <xsl:value-of select=". "/>  
  
  </cbc:ID>  
  
  </xsl:for-each>  
  
  <xsl:for-each select="cb:Postbox">  
  
    <cbc:Postbox>  
  
      <xsl:if test="@languageID">  
  
        <xsl:attribute name="languageID"><xsl:value-of  
select="@languageID"/></xsl:attribute>  
  
      </xsl:if>  
  
      <xsl:value-of select=". "/>  
  
    </cbc:Postbox>  
  
  </xsl:for-each>  
  
  <xsl:for-each select="cb:StreetName">  
  
    <cbc:StreetName>  
  
      <xsl:if test="@languageID">  
  
        <xsl:attribute name="languageID"><xsl:value-of  
select="@languageID"/></xsl:attribute>  
  
      </xsl:if>  
  
      <xsl:value-of select=". "/>  
  
    </cbc:StreetName>  
  
  </xsl:for-each>  
  
  <xsl:for-each select="cb:BuildingName">  
  
    <cbc:BuildingName>  
  
      <xsl:if test="@languageID">
```

```
    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select=". "/>

</cbc:BuildingName>

</xsl:for-each>

<xsl:for-each select="cb:BuildingNumber">

<cbc:BuildingNumber>

    <xsl:if test="@languageID">

        <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select=". "/>

</cbc:BuildingNumber>

</xsl:for-each>

<xsl:for-each select="cb:Department">

<cbc:Department>

    <xsl:if test="@languageID">

        <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

    </xsl:if>

    <xsl:value-of select=". "/>

</cbc:Department>

</xsl:for-each>

<xsl:for-each select="cb:CityName">

<cbc:CityName>
```

```
<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:CityName>

</xsl:for-each>

<xsl:for-each select="cb:PostalZone">

<cbc:PostalZone>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:PostalZone>

</xsl:for-each>

<xsl:for-each select="cb:CountrySubentity">

<cbc:CountrySubentity>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:CountrySubentity>

</xsl:for-each>

<xsl:for-each select="ca:AddressLine">
```

```

<cac:AddressLine>

    <xsl:for-each select="cb:Line">

        <cbc:Line>

            <xsl:if test="@languageID">
                <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>
            </xsl:if>
            <xsl:value-of select=". "/>
        </cbc:Line>

    </xsl:for-each>

</cac:AddressLine>

</xsl:for-each>

<xsl:for-each select="ca:Country">

    <cac:Country>

        <xsl:for-each select="ca:IdentificationCode">

            <cbc:IdentificationCode>

                <xsl:if test="@codeListID">
                    <xsl:attribute name="listID"><xsl:value-of
select="@codeListID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@codeListAgencyID">
                    <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@codeListAgencyName">
                    <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>
                </xsl:if>
            </cbc:IdentificationCode>
        </xsl:for-each>
    </cac:Country>
</xsl:for-each>

```

```

        </xsl:if>

        <xsl:if test="@codeListName">
            <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@codeListVersionID">
            <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@name">
            <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@languageID">
            <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@codeListURI">
            <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@codeListSchemeURI">
            <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

        </xsl:if>

        <xsl:value-of select=". "/>

    </cbc:IdentificationCode>

</xsl:for-each>

```

```

<xsl:for-each select="cb:Name">

    <cbc:Name>

        <xsl:if test="@languageID">
            <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

        </xsl:if>

        <xsl:value-of select=". "/>

    </cbc:Name>

</xsl:for-each>

</cac:Country>

</xsl:for-each>

</cac:Address>
</xsl:for-each>

</cac:FinancialInstitutionBranch>
</xsl:for-each>
<xsl:for-each
select="ca:Country">
    <cac:Country>
        <xsl:for-each
select="ca:IdentificationCode">

            <cbc:IdentificationCode>

                <xsl:if test="@codeListID">
                    <xsl:attribute name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListAgencyID">
                    <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListAgencyName">

```

```
<xsl:attribute name="listAgencyName"><xsl:value-of  
select="@codeListAgencyName"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@codeListName">  
  
    <xsl:attribute name="listName"><xsl:value-of  
select="@codeListName"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@codeListVersionID">  
  
    <xsl:attribute name="listVersionID"><xsl:value-of  
select="@codeListVersionID"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@name">  
  
    <xsl:attribute name="name"><xsl:value-of select="@name"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@languageID">  
  
    <xsl:attribute name="languageID"><xsl:value-of  
select="@languageID"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@codeListURI">  
  
    <xsl:attribute name="listURI"><xsl:value-of  
select="@codeListURI"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:if test="@codeListSchemeURI">  
  
    <xsl:attribute name="listSchemeURI"><xsl:value-of  
select="@codeListSchemeURI"/></xsl:attribute>  
  
</xsl:if>  
  
<xsl:value-of select=". "/>  
  
</cbc:IdentificationCode>  
    </xsl:for-each>
```

```

        <xsl:for-each>
select="cb:Name">
        <cbc:Name>

        <xsl:if test="@languageID">
            <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

        </xsl:if>

        <xsl:value-of select=".."/>

        </cbc:Name>
                </xsl:for-each>
                </cac:Country>
                </xsl:for-each>
                </cac:PayeeFinancialAccount>
                </xsl:for-each>
                </cac:PaymentMeans>
            </xsl:for-each>
            <xsl:for-each select="ca:PaymentTerms">
                <cac:PaymentTerms>
                    <xsl:for-each select="cb:Note">
                        <cbc:Note>
                            <xsl:if test="@languageID">
                                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                            </xsl:if>
                            <xsl:value-of select=".."/>
                        </cbc:Note>
                    </xsl:for-each>
                </cac:PaymentTerms>
            </xsl:for-each>
            <xsl:for-each select="ca:AllowanceCharge">
                <cac:AllowanceCharge>
                    <xsl:for-each select="cb:ChargeIndicator">
                        <cbc:ChargeIndicator>
                            <xsl:value-of select=".."/>
                        </cbc:ChargeIndicator>
                    </xsl:for-each>
                    <xsl:for-each select="ca:ReasonCode">
                        <cbc:AllowanceChargeReasonCode>
                            <xsl:if test="@codeListID">
                                <xsl:attribute
name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>
                            </xsl:if>
                            <xsl:if
test="@codeListAgencyID">

```

```

                <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>
                </xsl:if>
                <xsl:if
test="@codeListAgencyName">
                <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@codeListName">
                    <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@codeListVersionID">
                    <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if test="@name">
                        <xsl:attribute
name="name"><xsl:value-of select="@name"/></xsl:attribute>
                        </xsl:if>
                        <xsl:if test="@languageID">
                            <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                            </xsl:if>
                            <xsl:if test="@codeListURI">
                                <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>
                                </xsl:if>
                                <xsl:if
test="@codeListSchemeURI">
                                    <xsl:attribute
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>
                                    </xsl:if>
                                    <xsl:value-of select="."/>
                                    </cbc:AllowanceChargeReasonCode>
</xsl:for-each>
<xsl:for-each
select="cb:MultiplierFactorNumeric">
                            <cbc:MultiplierFactorNumeric>
                                <xsl:value-of select="."/>
                            </cbc:MultiplierFactorNumeric>
</xsl:for-each>
<xsl:for-each select="cb:Amount">
                            <cbc:Amount>
                                <xsl:if
test="@amountCurrencyID">
                                    <xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                                    </xsl:if>

```

```

                <xsl:value-of select="."/>
            </cbc:Amount>
        </xsl:for-each>
    </cac:AllowanceCharge>
</xsl:for-each>
<xsl:for-each select="ca:TaxTotal">
    <cac:TaxTotal>
        <xsl:for-each select="cb:TotalTaxAmount">
            <cbc:TaxAmount>
                <xsl:if
test="@amountCurrencyID">
                    <xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                </xsl:if>
                <xsl:value-of select="."/>
            </cbc:TaxAmount>
        </xsl:for-each>
        <xsl:for-each select="ca:TaxSubTotal">
            <cac:TaxSubtotal>
                <xsl:for-each
select="cb:TaxableAmount">
                    <cbc:TaxableAmount>
                        <xsl:if
test="@amountCurrencyID">
                            <xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                        </xsl:if>
                        <xsl:value-of
select="."/>
                    </cbc:TaxableAmount>
                </xsl:for-each>
                <xsl:for-each
select="cb:TaxAmount">
                    <cbc:TaxAmount>
                        <xsl:if
test="@amountCurrencyID">
                            <xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                        </xsl:if>
                        <xsl:value-of
select="."/>
                    </cbc:TaxAmount>
                </xsl:for-each>
                <xsl:for-each
select="ca:TaxCategory">
                    <cac:TaxCategory>
                        <xsl:for-each
select="ca:ID">
                            <cbc:ID>

```

```
<xsl:if test="@identificationSchemeID">

    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeName">

    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">

    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">

    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

    <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>
```

```

<xsl:value-of select=". "/>
                                         </cbc:ID>
</xsl:for-each>
<xsl:for-each
select="ca:TaxScheme">

    <cac:TaxScheme>
        <xsl:for-each select="ca:ID">
            <cbc:ID>
                <xsl:if test="@identificationSchemeID">
                    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeName">
                    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeAgencyID">
                    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeAgencyName">
                    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeVersionID">
                    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeDataURI">

```

```
    <xsl:attribute name="schemeDataURI"><xsl:value-of  
select="@identificationSchemeDataURI"/></xsl:attribute>  
  
    </xsl:if>  
  
    <xsl:if test="@identificationSchemeURI">  
  
        <xsl:attribute name="schemeURI"><xsl:value-of  
select="@identificationSchemeURI"/></xsl:attribute>  
  
        </xsl:if>  
  
        <xsl:value-of select="."/>  
  
    </cbc:ID>  
  
    </xsl:for-each>  
  
    <xsl:for-each select="ca:TaxTypeCode">  
  
        <cbc:TaxTypeCode>  
  
            <xsl:if test="@codeListID">  
  
                <xsl:attribute name="listID"><xsl:value-of  
select="@codeListID"/></xsl:attribute>  
  
            </xsl:if>  
  
            <xsl:if test="@codeListAgencyID">  
  
                <xsl:attribute name="listAgencyID"><xsl:value-of  
select="@codeListAgencyID"/></xsl:attribute>  
  
            </xsl:if>  
  
            <xsl:if test="@codeListAgencyName">  
  
                <xsl:attribute name="listAgencyName"><xsl:value-of  
select="@codeListAgencyName"/></xsl:attribute>  
  
            </xsl:if>  
  
            <xsl:if test="@codeListName">  
  
                <xsl:attribute name="listName"><xsl:value-of  
select="@codeListName"/></xsl:attribute>  
  
            </xsl:if>
```

```
<xsl:if test="@codeListVersionID">

    <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@name">

    <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

</xsl:if>

<xsl:if test="@languageID">

    <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListURI">

    <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@codeListSchemeURI">

    <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select="."/>

</cbc:TaxTypeCode>

</xsl:for-each>

</cac:TaxScheme>
                </xsl:for-each>
                    </cac:TaxCategory>
                        <xsl:for-each>
                            </cac:TaxSubtotal>
                                </xsl:for-each>
                            </cac:TaxTotal>
                        </xsl:for-each>
```

```

<xsl:for-each select="ca:LegalTotal">
    <cac:LegalMonetaryTotal>
        <xsl:for-each
            select="cb:LineExtensionTotalAmount">
                <cbc:LineExtensionAmount>
                    <xsl:if
                        test="@amountCurrencyID">
                            <xsl:attribute
                                name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                            </xsl:if>
                            <xsl:value-of select="."/>
                        </cbc:LineExtensionAmount>
                    </xsl:for-each>
                    <xsl:for-each
                        select="cb:TaxExclusiveTotalAmount">
                            <cbc:TaxExclusiveAmount>
                                <xsl:if
                                    test="@amountCurrencyID">
                                        <xsl:attribute
                                            name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                                        </xsl:if>
                                        <xsl:value-of select="."/>
                                    </cbc:TaxExclusiveAmount>
                                </xsl:for-each>
                                <xsl:for-each
                                    select="cb:TaxInclusiveTotalAmount">
                                        <cbc:PayableAmount>
                                            <xsl:if
                                                test="@amountCurrencyID">
                                                    <xsl:attribute
                                                        name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                                                    </xsl:if>
                                                    <xsl:value-of select="."/>
                                                </cbc:PayableAmount>
                                            </xsl:for-each>
                                            </cac:LegalMonetaryTotal>
                                        </xsl:for-each>
                                        <xsl:for-each select="ca:InvoiceLine">
                                            <cac:InvoiceLine>
                                                <xsl:for-each select="ca:ID">
                                                    <cbc:ID>
                                                        <xsl:if
                                                            test="@identificationSchemeID">
                                                                <xsl:attribute
                                                                    name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
                                                                </xsl:if>
                                                                <xsl:if
                                                                    test="@identificationSchemeName">
                                                                        <xsl:attribute
                                                                            name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>

```

```

        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyID">
            <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
            </xsl:if>
            <xsl:if
test="@identificationSchemeAgencyName">
            <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
            </xsl:if>
            <xsl:if
test="@identificationSchemeVersionID">
            <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
            </xsl:if>
            <xsl:if
test="@identificationSchemeDataURI">
            <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
            </xsl:if>
            <xsl:if
test="@identificationSchemeURI">
            <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
            </xsl:if>
            <xsl:value-of select="."/>
            </cbc:ID>
        </xsl:for-each>
        <xsl:for-each select="cb:InvoicedQuantity">
            <cbc:InvoicedQuantity>
                <xsl:attribute
name="unitCode"><xsl:value-of select="@quantityUnitCode"/></xsl:attribute>
                <xsl:value-of select="."/>
            </cbc:InvoicedQuantity>
        </xsl:for-each>
        <xsl:for-each
select="cb:LineExtensionAmount">
            <cbc:LineExtensionAmount>
                <xsl:if
test="@amountCurrencyID">
                    <xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:value-of select="."/>
                </cbc:LineExtensionAmount>

```

```

    </xsl:for-each>
    <xsl:for-each select="ca:OrderLineReference">
        <cac:OrderLineReference>
            <xsl:for-each
select="ca:BuyersLineID">
                <cbc:LineID>
                    <xsl:if
test="@identificationSchemeID">
                        <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@identificationSchemeName">
                        <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@identificationSchemeAgencyID">
                        <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@identificationSchemeAgencyName">
                        <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@identificationSchemeVersionID">
                        <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@identificationSchemeDataURI">
                        <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
                    </xsl:if>
                    <xsl:if
test="@identificationSchemeURI">
                        <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
                    </xsl:if>
                    <xsl:value-of
select="."/>
                </cbc:LineID>
            </xsl:for-each>

```

```

<xsl:for-each
select="ca:SellersLineID">
    <cbc:SalesOrderLineID>
        <xsl:if
test="@identificationSchemeID">
            <xsl:attribute
name="schemeID"><xsl:value-of select="@identificationSchemeID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeName">
            <xsl:attribute
name="schemeName"><xsl:value-of select="@identificationSchemeName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyID">
            <xsl:attribute
name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeAgencyName">
            <xsl:attribute
name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeVersionID">
            <xsl:attribute
name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeDataURI">
            <xsl:attribute
name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
        </xsl:if>
        <xsl:if
test="@identificationSchemeURI">
            <xsl:attribute
name="schemeURI"><xsl:value-of select="@identificationSchemeURI"/></xsl:attribute>
        </xsl:if>
        <xsl:value-of
select="."/>
            </cbc:SalesOrderLineID>
        </xsl:for-each>
        <xsl:for-each
select="ca:LineStatusCode">
            <cbc:LineStatusCode>

```

```

<xsl:if
test="@codeListID">
    <xsl:attribute
name="listID"><xsl:value-of select="@codeListID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@codeListAgencyID">
    <xsl:attribute
name="listAgencyID"><xsl:value-of select="@codeListAgencyID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@codeListAgencyName">
    <xsl:attribute
name="listAgencyName"><xsl:value-of select="@codeListAgencyName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@codeListName">
    <xsl:attribute
name="listName"><xsl:value-of select="@codeListName"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@codeListVersionID">
    <xsl:attribute
name="listVersionID"><xsl:value-of select="@codeListVersionID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@name">
    <xsl:attribute
name="name"><xsl:value-of select="@name"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@languageID">
    <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@codeListURI">
    <xsl:attribute
name="listURI"><xsl:value-of select="@codeListURI"/></xsl:attribute>
</xsl:if>
<xsl:if
test="@codeListSchemeURI">
    <xsl:attribute
name="listSchemeURI"><xsl:value-of select="@codeListSchemeURI"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select="."/>
    </cbc:LineStatusCode>
</xsl:for-each>

```

```

<xsl:for-each
select="ca:OrderReference">
    <cac:OrderReference>
        <xsl:for-each
select="ca:BuyersID">
            <cbc:ID>

                <xsl:if test="@identificationSchemeID">
                    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@identificationSchemeName">
                    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@identificationSchemeAgencyID">
                    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@identificationSchemeAgencyName">
                    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@identificationSchemeVersionID">
                    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@identificationSchemeDataURI">
                    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>
                </xsl:if>

                <xsl:if test="@identificationSchemeURI">

```

```

<xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>                                </cbc:ID>
</xsl:for-each>
<xsl:for-each
select="ca:SellersID">

<cbc:SalesOrderID>

<xsl:if test="@identificationSchemeID">

<xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeName">

<xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

<xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">

<xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">

<xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

```

```

<xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

<xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:SalesOrderID>
</xsl:for-each>
<xsl:for-each
select="ca:GUID">
<cbc:UUID>

<xsl:if test="@identificationSchemeID">

<xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeName">

<xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">

<xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">

<xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">

```

```

<xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">

<xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">

<xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select=". "/>

</cbc:UUID>
</xsl:for-each>
<xsl:for-each
select="cb:IssueDate">

<cbc:IssueDate>
<xsl:value-of select=". "/>
</cbc:IssueDate>
</xsl:for-each>
</cac:OrderReference>
</xsl:for-each>
</cac:OrderLineReference>
</xsl:for-each>
<xsl:for-each select="ca:TaxTotal">
<cac:TaxTotal>
<xsl:for-each
select="cb:TotalTaxAmount">
<cbc:TaxAmount>
<xsl:if
test="@amountCurrencyID">
<xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
</xsl:if>
<xsl:value-of
select=". "/>
</cbc:TaxAmount>

```

```

        </xsl:for-each>
        <xsl:for-each

select="ca:TaxSubTotal">
            <cac:TaxSubtotal>
                <xsl:for-each

select="cb:TaxableAmount">

        <cbc:TaxableAmount>

        <xsl:if test="@amountCurrencyID">
            <xsl:attribute name="currencyID"><xsl:value-of
select="@amountCurrencyID"/></xsl:attribute>
        </xsl:if>

        <xsl:value-of select=". "/>
    </cbc:TaxableAmount>
        </xsl:for-each>
        <xsl:for-each

select="cb:TaxAmount">

    <cbc:TaxAmount>

    <xsl:if test="@amountCurrencyID">
        <xsl:attribute name="currencyID"><xsl:value-of
select="@amountCurrencyID"/></xsl:attribute>
    </xsl:if>

    <xsl:value-of select=". "/>
    </cbc:TaxAmount>
        </xsl:for-each>
        <xsl:for-each

select="ca:TaxCategory">

    <cac:TaxCategory>
        <xsl:for-each select="ca:ID">

            <cbc:ID>
                <xsl:if test="@identificationSchemeID">
                    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>

```

```
</xsl:if>

<xsl:if test="@identificationSchemeName">
    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyID">
    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">
    <xsl:attribute name="schemeAgencyName"><xsl:value-of
select="@identificationSchemeAgencyName"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeVersionID">
    <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeDataURI">
    <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

</xsl:if>

<xsl:if test="@identificationSchemeURI">
    <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

</xsl:if>

<xsl:value-of select="."/>

</cbc:ID>

</xsl:for-each>
```

```

<xsl:for-each select="cb:Percent">

    <cbc:Percent>
        <xsl:value-of select="."/>
    </cbc:Percent>
</xsl:for-each>

<xsl:for-each select="ca:TaxScheme">

    <cac:TaxScheme>
        <xsl:for-each select="ca:ID">

            <cbc:ID>
                <xsl:if test="@identificationSchemeID">
                    <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeName">
                    <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeAgencyID">
                    <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeAgencyName">
                    <xsl:attribute name="schemeAgencyName"><xsl:value-
of select="@identificationSchemeAgencyName"/></xsl:attribute>
                </xsl:if>
                <xsl:if test="@identificationSchemeVersionID">

```

```

        <xsl:attribute name="schemeVersionID"><xsl:value-of
select="@identificationSchemeVersionID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@identificationSchemeDataURI">

            <xsl:attribute name="schemeDataURI"><xsl:value-of
select="@identificationSchemeDataURI"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@identificationSchemeURI">

                <xsl:attribute name="schemeURI"><xsl:value-of
select="@identificationSchemeURI"/></xsl:attribute>

                </xsl:if>

                <xsl:value-of select=".."/>

            </cbc:ID>

        </xsl:for-each>

        <xsl:for-each select="ca:TaxTypeCode">

            <cbc:TaxTypeCode>

                <xsl:if test="@codeListID">

                    <xsl:attribute name="listID"><xsl:value-of
select="@codeListID"/></xsl:attribute>

                    </xsl:if>

                    <xsl:if test="@codeListAgencyID">

                        <xsl:attribute name="listAgencyID"><xsl:value-of
select="@codeListAgencyID"/></xsl:attribute>

                        </xsl:if>

                        <xsl:if test="@codeListAgencyName">

                            <xsl:attribute name="listAgencyName"><xsl:value-of
select="@codeListAgencyName"/></xsl:attribute>

                            </xsl:if>


```

```

<xsl:if test="@codeListName">

    <xsl:attribute name="listName"><xsl:value-of
select="@codeListName"/></xsl:attribute>

    </xsl:if>

    <xsl:if test="@codeListVersionID">

        <xsl:attribute name="listVersionID"><xsl:value-of
select="@codeListVersionID"/></xsl:attribute>

        </xsl:if>

        <xsl:if test="@name">

            <xsl:attribute name="name"><xsl:value-of
select="@name"/></xsl:attribute>

            </xsl:if>

            <xsl:if test="@languageID">

                <xsl:attribute name="languageID"><xsl:value-of
select="@languageID"/></xsl:attribute>

                </xsl:if>

                <xsl:if test="@codeListURI">

                    <xsl:attribute name="listURI"><xsl:value-of
select="@codeListURI"/></xsl:attribute>

                    </xsl:if>

                    <xsl:if test="@codeListSchemeURI">

                        <xsl:attribute name="listSchemeURI"><xsl:value-of
select="@codeListSchemeURI"/></xsl:attribute>

                        </xsl:if>

                        <xsl:value-of select=". "/>

                    </xsl:if>

                </xsl:if>

            </xsl:if>

        </xsl:if>

    </xsl:if>

</cbc:TaxTypeCode>

</xsl:for-each>

</cac:TaxScheme>

```

```

</xsl:for-each>

</cac:TaxCategory>
    </xsl:for-each>
        </cac:TaxSubtotal>
            </xsl:for-each>
                </cac:TaxTotal>
            </xsl:for-each>
            <xsl:for-each select="ca:Item">
                <cac:Item>
                    <xsl:for-each
select="cb:Description">
                        <cbc:Description>
                            <xsl:if
test="@languageID">
                                <xsl:attribute
name="languageID"><xsl:value-of select="@languageID"/></xsl:attribute>
                            </xsl:if>
                            <xsl:value-of
select="."/>
                        <cbc:Description>
                    </xsl:for-each>
                    <xsl:for-each
select="ca:SellersItemIdentification">
                        <cac:SellersItemIdentification>
                            <xsl:for-each
select="ca:ID">
                                <cbc:ID>
                                    <xsl:if test="@identificationSchemeID">
                                        <xsl:attribute name="schemeID"><xsl:value-of
select="@identificationSchemeID"/></xsl:attribute>
                                    </xsl:if>
                                    <xsl:if test="@identificationSchemeName">
                                        <xsl:attribute name="schemeName"><xsl:value-of
select="@identificationSchemeName"/></xsl:attribute>
                                    </xsl:if>
                                    <xsl:if test="@identificationSchemeAgencyID">
                                        <xsl:attribute name="schemeAgencyID"><xsl:value-of
select="@identificationSchemeAgencyID"/></xsl:attribute>
                                    </xsl:if>
                                </cbc:ID>
                            </xsl:for-each>
                        </cac:SellersItemIdentification>
                    </xsl:for-each>
                </cac:Item>
            </xsl:for-each>
        </cac:TaxSubtotal>
    </xsl:for-each>
</cac:TaxCategory>

```

```

</xsl:if>

<xsl:if test="@identificationSchemeAgencyName">
  <xsl:attribute name="schemeAgencyName"><xsl:value-of
  select="@identificationSchemeAgencyName"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeVersionID">
  <xsl:attribute name="schemeVersionID"><xsl:value-of
  select="@identificationSchemeVersionID"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeDataURI">
  <xsl:attribute name="schemeDataURI"><xsl:value-of
  select="@identificationSchemeDataURI"/></xsl:attribute>
</xsl:if>

<xsl:if test="@identificationSchemeURI">
  <xsl:attribute name="schemeURI"><xsl:value-of
  select="@identificationSchemeURI"/></xsl:attribute>
</xsl:if>

<xsl:value-of select=". "/>                                </cbc:ID>
</xsl:for-each>

</cac:SellersItemIdentification>                         </xsl:for-each>
  </cac:Item>                                         </xsl:for-each>
  </xsl:for-each>                                     <xsl:for-each select="ca:Item/ca:BasePrice">
    <cac:Price>                                       <cac:Price>
      <xsl:for-each
select="cb:PriceAmount">                                <xsl:attribute
  <cbc:PriceAmount>                                 name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
  <xsl:if
test="@amountCurrencyID">                                </xsl:if>
    <xsl:attribute
name="currencyID"><xsl:value-of select="@amountCurrencyID"/></xsl:attribute>
  </xsl:if>

```

```
<xsl:value-of  
select=". "/>  
    </cbc:PriceAmount>  
    </xsl:for-each>  
    <xsl:for-each  
select="cb:BaseQuantity">  
        <cbc:BaseQuantity>  
            <xsl:attribute  
name="unitCode"><xsl:value-of select="@quantityUnitCode"/></xsl:attribute>  
                <xsl:value-of  
select=". "/>  
                    <cbc:BaseQuantity>  
                        </xsl:for-each>  
                        <cac:Price>  
                            </xsl:for-each>  
                            </cac:InvoiceLine>  
                        </xsl:for-each>  
                    </Invoice>  
                </xsl:for-each>  
            </xsl:template>  
</xsl:stylesheet>
```

## UBL 1.0 SBS Invoice example