



Web Services ReliableMessaging Policy Assertion (WS-RM Policy)

Committee Draft ~~05, February 1, 2007~~, ~~August 11, 2006~~

Document identifier:

wsrmp-1.1-spec-cd-054

Location:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05608/wsrmp-1.1-spec-cd-04.pdf>

Editors:

Doug Davis, IBM <dug@us.ibm.com>

Anish Karmarkar, Oracle <Anish.Karmarkar@oracle.com>

Gilbert Pilz, BEA <gpilz@bea.com>

Ümit Yalçinalp, SAP <umit.yalcinalp@sap.com>

Contributors:

See the Acknowledgments (Appendix A).

Abstract:

This specification describes a domain-specific policy assertion for WS-ReliableMessaging [WS-RM] that that can be specified within a policy alternative as defined in WS-Policy Framework [WS-Policy].

By using the XML [XML], SOAP [SOAP 1.1], [SOAP 1.2] and WSDL [WSDL 1.1] extensibility models, the WS* specifications are designed to be composed with each other to provide a rich Web services environment. This by itself does not provide a negotiation solution for Web services. This is a building block that is used in conjunction with other Web service and application-specific protocols to accommodate a wide variety of policy exchange models.

Status:

This document was last revised or approved by the WS-RX on the above date. The level of approval is also listed above. Check the current location noted above for possible later revisions of this document. This document is updated periodically on no particular schedule. Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <http://www.oasis-open.org/committees/ws-rx>. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/ws-rx/ipr.php>). The non-normative errata page for this specification is located at <http://www.oasis-open.org/committees/ws-rx>.

Table of Contents

38			
39	1	Introduction.....	3
40	1.1	Goals and Requirements.....	3
41	1.2	Notational Conventions.....	3
42	1.3	Namespace.....	4
43	1.4	Compliance.....	4
44	2	RM Policy Assertions.....	5
45	2.1	Assertion Model	5
46	2.2	Normative Outline.....	5
47	2.3	Assertion Attachment.....	6
48	2.4	Assertion Example.....	8
49	2.5	Sequence Security Policy.....	8
50	3	Security Considerations.....	10
51	4	References.....	11
52	4.1	Normative.....	11
53	4.2	Non Normative.....	12
54		Appendix A. Acknowledgments.....	13
55		Appendix B. XML Schema.....	14
56		Appendix C. Revision History.....	16
57		Appendix D. Notices.....	19

1 Introduction

This specification defines a domain-specific policy assertion for reliable messaging for use with WS-Policy and WS-ReliableMessaging.

1.1 Goals and Requirements

1.1.1 Requirements

1.2 Notational Conventions

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [KEYWORDS].

This specification uses the following syntax to define normative outlines for messages:

- The syntax appears as an XML instance, but values in italics indicate data types instead of values.
- Characters are appended to elements and attributes to indicate cardinality:
 - "?" (0 or 1)
 - "*" (0 or more)
 - "+" (1 or more)
- The character "|" is used to indicate a choice between alternatives.
- The characters "[" and "]" are used to indicate that contained items are to be treated as a group with respect to cardinality or choice.
- An ellipsis (i.e. "...") indicates a point of extensibility that allows other child, or attribute, content. Additional children and/or attributes MAY be added at the indicated extension points but MUST NOT contradict the semantics of the parent and/or owner, respectively. If an extension is not recognized it SHOULD be ignored.
- XML namespace prefixes (See Section 1.3) are used to indicate the namespace of the element being defined.

Elements and Attributes defined by this specification are referred to in the text of this document using XPath 1.0 [XPATH 1.0] expressions. Extensibility points are referred to using an extended version of this syntax:

- An element extensibility point is referred to using {any} in place of the element name. This indicates that any element name can be used, from any namespace other than the wsrn: namespace.
- An attribute extensibility point is referred to using @{any} in place of the attribute name. This indicates that any attribute name can be used, from any namespace other than the wsrn: namespace.

1.3 Namespace

The XML namespace [XML-ns] URI that MUST be used by implementations of this specification is:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702608>

Dereferencing the above URI will produce the Resource Directory Description Language [RDDL 2.0] document that describes this namespace.

Table 1 lists the XML namespaces that are used in this specification. The choice of any namespace prefix is arbitrary and not semantically significant.

Table 1

Prefix	Namespace	Specification
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL 1.1]
wsp	http://schemas.xmlsoap.org/ws/2004/09/policy	[WS-Policy]
wsrmp	http://docs.oasis-open.org/ws-rx/wsrmp/200702	This specification.
wsu	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd	WS-Security-Utility Schema

1.4 Compliance

An implementation is not compliant with this specification if it fails to satisfy one or more of the MUST or REQUIRED level requirements defined herein. A SOAP Node MUST NOT use the XML namespace identifier for this specification (listed in Section 1.3) within SOAP Envelopes unless it is compliant with this specification.

Normative text within this specification takes precedence over normative outlines, which in turn take precedence over the XML Schema [XML-Schema Part1, XML-Schema Part2] descriptions.

2 RM Policy Assertions

WS-Policy Framework and WS-Policy Attachment [WS-PolicyAttachment] collectively define a framework, model and grammar for expressing the requirements, and general characteristics of entities in an XML Web services-based system. To enable an RM Destination and an RM Source to describe their requirements for a given Sequence, this specification defines a single RM policy assertion that leverages the WS-Policy framework.

2.1 Assertion Model

The RM policy assertion indicates that the RM Source and RM Destination MUST use WS-ReliableMessaging to ensure reliable delivery of messages. Specifically, the WS-ReliableMessaging protocol determines invariants maintained by the reliable messaging endpoints and the directives used to track and manage the delivery of a Sequence of messages.

2.2 Normative Outline

The normative outline for the RM assertion is:

```
<wsrmp:RMAssertion [wsp:Optional="true"]? ... >
  <wsp:Policy>
    [ <wsrmp:SequenceSTR/> |
      <wsrmp:SequenceTransportSecurity/> ] ?
    <wsrmp:DeliveryAssurance>
      <wsp:Policy>
        [ <wsrmp:ExactlyOnce/> |
          <wsrmp:AtLeastOnce/> |
          <wsrmp:AtMostOnce/> ]
        <wsrmp:InOrder/> ?
      </wsp:Policy>
    </wsrmp:DeliveryAssurance> ?
  </wsp:Policy>
  ...
</wsrmp:RMAssertion>
```

The following describes the content model of the RMAssertion element, additional, normative constraints on the outline listed above:

/wsrmp:RMAssertion

A policy assertion that specifies that WS-ReliableMessaging protocol MUST be used when sending messages.

/wsrmp:RMAssertion/@wsp:Optional="true"

Per WS-Policy, this is compact notation for two policy alternatives, one with and one without the assertion. The intuition is that the behavior indicated by the assertion is optional, or in this case, that WS-ReliableMessaging MAY be used.

/wsrmp:RMAssertion/wsp:Policy

This required element allows for the inclusion of nested policy assertions.

/wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceSTR

When present, this assertion defines the requirement that an RM Sequence MUST be bound to an explicit token that is referenced from a `wsse:SecurityTokenReference` in the `CreateSequence` message. See section 2.5.1.

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceTransportSecurity`

When present, this assertion defines the requirement that an RM Sequence MUST be bound to the session(s) of the underlying transport-level protocol used to carry the `CreateSequence` and `CreateSequenceResponse` message. When present, this assertion MUST be used in conjunction with the `sp:TransportBinding` assertion, see section 2.5.2.

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance`

This expression, which may be omitted, describes the message delivery quality of service between the RM and application layer. When used by an RM Destination it expresses the delivery assurance in effect between the RM Destination and its corresponding application destination, and it also indicates requirements on any RM Source that transmits messages to this RM destination. Conversely when used by an RM Source it expresses the delivery assurance in effect between the RM Source and its corresponding application source, as well as indicating requirements on any RM Destination that receives messages from this RM Source. In either case the delivery assurance does not affect the messages transmitted on the wire. Absence of this expression from a `wsrmp:RMAssertion` policy assertion simply means that the endpoint has chosen not to advertise its delivery assurance characteristics. Note that when there are multiple policy alternatives of the RM Assertion, the Delivery Assurance on each MUST NOT conflict.

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy`

This required element identifies additional requirements for the use of the `wsrmp:DeliveryAssurance`.

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:ExactlyOnce`

This expresses the `ExactlyOnce` Delivery Assurance defined in [1].

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtLeastOnce`

This expresses the `AtLeastOnce` Delivery Assurance defined in [1].

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtMostOnce`

This expresses the `AtMostOnce` Delivery Assurance defined in [1].

`/wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:InOrder`

This expresses the `InOrder` Delivery Assurance defined in [1].

`/wsrmp:RMAssertion/{any}`

This is an extensibility mechanism to allow different (extensible) types of information, based on a schema, to be passed.

`/wsrmp:RMAssertion/@{any}`

This is an extensibility mechanism to allow different (extensible) types of information, based on a schema, to be passed.

2.3 Assertion Attachment

The RM policy assertion is allowed to have the following Policy Subjects [[WS-PolicyAttachment](#)]:

- Endpoint Policy Subject

● Message Policy Subject

WS-PolicyAttachment defines a set of WSDL/1.1 policy attachment points for each of the above Policy Subjects. Since an RM policy assertion specifies a concrete behavior, it MUST NOT be attached to the abstract WSDL policy attachment points.

The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an RM policy assertion but which MUST NOT have RM policy assertions attached:

- wsdl:message
- wsdl:portType/wsdl:operation/wsdl:input
- wsdl:portType/wsdl:operation/wsdl:output
- wsdl:portType/wsdl:operation/wsdl:fault
- wsdl:portType

The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an RM policy assertion and which MAY have RM policy assertions attached:

- wsdl:port
- wsdl:binding
- wsdl:binding/wsdl:operation/wsdl:input
- wsdl:binding/wsdl:operation/wsdl:output
- wsdl:binding/wsdl:operation/wsdl:fault

If an RM policy assertion is attached to any of:

- wsdl:binding/wsdl:operation/wsdl:input
- wsdl:binding/wsdl:operation/wsdl:output
- wsdl:binding/wsdl:operation/wsdl:fault

then an RM policy assertion, specifying `wsp:Optional=true` MUST be attached to the corresponding `wsdl:binding` or `wsdl:port`, indicating that the endpoint supports WS-RM. Any messages, regardless of whether they have an attached Message Policy Subject RM policy assertion, MAY be sent to that endpoint using WS-RM. Additionally, the receiving endpoint MUST NOT reject any message belonging to a Sequence, simply because there was no Message Policy Subject RM policy assertion attached to that message. There might be certain RM implementations that are incapable of applying RM Quality of Service (QoS) semantics on a per-message basis. In order to ensure the broadest interoperability, when an endpoint decorates its WSDL with RM policy assertions using Message Policy Subject, it MUST also be prepared to accept that all messages sent to that endpoint might be sent within the context of an RM Sequence, regardless of whether the corresponding `wsdl:input`, `wsdl:output` or `wsdl:fault` had an attached RM policy assertion.

Rather than turn away messages that were unnecessarily sent with RM semantics, the receiving endpoint described by the WSDL MUST accept these messages.

By attaching an RM policy assertion that specifies `wsp:Optional="true"` to the corresponding endpoint that has attached RM policy assertions at the Message Policy Subject level, the endpoint is describing the above constraint in policy.

In the case where an optional RM Assertion applies to an output message, there is no requirement on the client to support an RM Destination implementation

2.4 Assertion Example

Table 2 lists an example use of the RM policy assertion.

Table 2: Example policy with RM policy assertion

```
(01)<wsdl:definitions
(02)   targetNamespace="example.com"
(03)   xmlns:tns="example.com"
(04)   xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
(05)   xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
(06)   xmlns:wsrmp="http://docs.oasis-open.org/ws-rx/wsrmp/200702608"
(07)   xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-
wss-wssecurity-utility-1.0.xsd">
(08)
(09)   <wsp:UsingPolicy wsdl:required="true" />
(10)
(11)   <wsp:Policy wsu:Id="MyPolicy" >
(12)     <wsrmp:RMAssertion/>
(13)     <wsp:Policy/>
(14)   </wsrmp:RMAssertion/> <!-- omitted assertions -->
(15)   <!-- omitted assertions --4> </wsp:Policy>
(16) </wsp:Policy>5>
(16) <!-- omitted elements -->
(17)
(18) <!-- omitted elements --wsdl:binding-name="MyBinding"-
type="tns:MyPortType">
(19)   <wsp:PolicyReference URI="#MyPolicy" />
(20)   <wsdl:binding name="MyBinding" type="tns:MyPortType" <!-- omitted
elements -->
(21)   <wsp:PolicyReference URI="#MyPolicy" /></wsdl:binding>
(22)   <!-- omitted elements -->
(23) </wsdl:binding></wsdl:definitions>
(24)
(25)</wsdl:definitions>
```

Line (09) in Table 2 indicates that WS-Policy is in use as a required extension.

Lines (11-16) are a policy expression that includes a RM policy assertion (lines 12-14) are a policy expression that includes a RM policy assertion (Line 12) to indicate that WS-ReliableMessaging must be used.

Lines (20-23) are a WSDL binding. Line (21) indicates that the policy in lines (11-16) are a WSDL binding. Line (19) indicates that the policy in Lines (11-14) applies to this binding, specifically indicating that WS-ReliableMessaging must be used over all the messages in the binding.

2.5 Sequence Security Policy

WS-SecurityPolicy [SecurityPolicy] provides a framework and grammar for expressing the security requirements and characteristics of entities in a XML web services based system. The following assertions MAY be used in conjunction with WS-SecurityPolicy to express additional security requirements particular to RM Sequences.

2.5.1 RM Assertion with Sequence STR Assertion

This version of the RM assertion includes an assertion that defines the requirement that an RM Sequence MUST be bound to an explicit token that is referenced from a wsse:SecurityTokenReference in the CreateSequence message.

275 This assertion MUST apply to [Endpoint Policy Subject]. The normative outline for this form of the
276 Sequence STR Assertion is: ~~is-assertion MUST NOT be used for an endpoint that does not also use the-~~
277 ~~RM-assertion:~~

```
278 <wsrmp:RMAssertion [wsp:Optional="true"]? ...>  
279 <wsp:Policy>  
280 <wsrmp:SequenceSTR/>  
281 <wsp:Policy>  
282 </wsrmp:RMAssertion>
```

283 The following describes the content model of the SequenceSTR element.

284 ~~The normative outline for the Sequence STR Assertion is:~~

```
285 <wsrmp:SequenceSTR [wsp:Optional="true"]? ... />
```

286 /wsrmp:SequenceSTR

287 A policy assertion that specifies security requirements which MUST be used with an RM Sequence that
288 are particular to WS-RM and beyond what can be expressed in WS-SecurityPolicy.

289 **2.5.2 RM Assertion with Sequence Transport Security Assertion**

290 This version of the RM assertion includes the requirement that an RM Sequence MUST be bound to the
291 session(s) of the underlying transport-level security protocol (e.g. SSL/TLS) used to carry the
292 CreateSequence and CreateSequenceResponse messages.

293 This assertion MUST apply to [Endpoint Policy Subject]. This assertion MUST be used in conjunction with
294 the sp:TransportBinding assertion that requires the use of some transport-level security mechanism
295 (e.g. sp:HttpsToken).

296 The normative outline for this form of the RM Assertion with the Sequence Transport Security Assertion is:

```
297 <wsp:Policy>  
298 <wsp:ExactlyOne>  
299 <wsp:All>  
300 <wsrm:RMAssertion [wsp:Optional="true"]> ...>  
301 <wsp:Policy>  
302 <wsrmp:SequenceTransportSecurity/>  
303 </wsp:Policy>  
304 </wsrm:RMAssertion>  
305 <sp:TransportBinding ...>  
306 ...  
307 </sp:TransportBinding>  
308 <wsp:All>  
309 <wsp:ExactlyOne>  
310 </wsp:Policy>
```

311 The following describes the content model of the SequenceTransportSecurity element.

312 /wsrm:SequenceSTR /@wsp:Optional="true"

313 ~~Per WS-Policy, this is compact notation for two policy alternatives, one with and one without the assertion.~~
314 ~~The intuition is that the behavior indicated by the assertion is optional, or in this case, that the RM-~~
315 ~~Sequence binding to a specific token MAY be used.~~

1.1.1 Sequence Transport Security Assertion

~~This assertion defines the requirement that an RM Sequence MUST be bound to the session(s) of the underlying transport-level security protocol (e.g. SSL/TLS) used to carry the CreateSequence and CreateSequenceResponse messages.~~

~~This assertion MUST apply to [Endpoint Policy Subject]. This assertion is effectively meaningless unless it occurs in conjunction with the RMAssertion and a sp:TransportBinding assertion that requires the use of some transport-level security mechanism (e.g. sp:HttpsToken).~~

~~The normative outline for the Sequence Transport Security Assertion is:~~

```
<wsrmp:SequenceTransportSecurity [wsp:Optional="true"]? ... />
```

~~/wsrmp:SequenceTransportSecurity~~

~~A policy assertion that specifies that any Sequences targeted to the indicated endpoint MUST be bound to the underlying session(s) of the transport-level security used to carry messages related to the Sequence.~~

~~This form of the RM Assertion says that an endpoint MAY have RM as an option but always requires HTTPS to be used. All the SequenceTransportSecurity assertion indicates is that RM's rules for protecting the Sequence over TLS are followed.~~

~~/wsrmp:SequenceTransportSecurity /@wsp:Optional="true"~~

~~Per WS-Policy, this is compact notation for two policy alternatives, one with and one without the assertion. The meaning is that the behavior indicated by the assertion is optional, or in this case, that the binding of RM Sequences to transport-level security sessions MAY be used.~~

3 Security Considerations

It is strongly RECOMMENDED that policies and assertions be signed to prevent tampering.

It is RECOMMENDED that policies SHOULD NOT be accepted unless they are signed and have an associated security token to specify the signer has proper claims for the given policy. That is, a relying party shouldn't rely on a policy unless the policy is signed and presented with sufficient claims to pass the relying parties acceptance criteria.

It should be noted that the mechanisms described in this document could be secured as part of a SOAP message using WS-Security [[WS-Security](#)] or embedded within other objects using object-specific security mechanisms.

4 References

4.1 Normative

[KEYWORDS]

S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," RFC 2119, Harvard University, March 1997.

<http://www.ietf.org/rfc/rfc2119.txt>

[SOAP 1.1]

W3C Note, "SOAP: Simple Object Access Protocol 1.1" 08 May 2000.

<http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP 1.2]

W3C Recommendation, "SOAP Version 1.2 Part 1: Messaging Framework" June 2003.

<http://www.w3.org/TR/2003/REC-soap12-part1-20030624/>

[URI]

T. Berners-Lee, R. Fielding, L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax," RFC 3986, MIT/LCS, U.C. Irvine, Xerox Corporation, January 2005.

<http://ietf.org/rfc/rfc3986>

[WS-RM]

OASIS WS-RX Technical Committee Draft, "Web Services Reliable Messaging (WS-ReliableMessaging)," ~~August~~September 2005.

<http://docs.oasis-open.org/ws-rx/wsrp/200702/wsrp-1.1-spec-cd-05.pdf>

[WS-Policy]

W3C Member Submission, "Web Services Policy Framework (WS-Policy)," April 2006.

<http://www.w3.org/Submission/2006/SUBM-WS-Policy-20060425/>

[WS-PolicyAttachment]

W3C Member Submission, "Web Services Policy Attachment (WS-PolicyAttachment)," April 2006.

<http://www.w3.org/Submission/2006/SUBM-WS-PolicyAttachment-20060425/>

[WSDL 1.1]

W3C Note, "Web Services Description Language (WSDL 1.1)," 15 March 2001.

<http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XML]

W3C Recommendation, "Extensible Markup Language (XML) 1.0 (~~Fourth Edition~~). ~~September 2006~~Second Edition", ~~October 2000~~.

<http://www.w3.org/TR/REC-xml/>

378 **[XML-ns]**

379 W3C Recommendation, "Namespaces in XML," 14 January 1999.

380 <http://www.w3.org/TR/1999/REC-xml-names-19990114/>

381 **[XML-Schema Part1]**

382 W3C Recommendation, "XML Schema Part 1: Structures," ~~October 2004~~ May 2001.

383 <http://www.w3.org/TR/xmlschema-1/>

384 **[XML-Schema Part2]**

385 W3C Recommendation, "XML Schema Part 2: Datatypes," ~~October 2004~~ May 2001.

386 <http://www.w3.org/TR/xmlschema-2/>

387 **[XPath 1.0]**

388 W3C Recommendation, "XML Path Language (XPath) Version 1.0," 16 November 1999.

389 <http://www.w3.org/TR/xpath>

390 **4.2 Non Normative**

391 **[RDDL 2.0]**

392 Jonathan Borden, Tim Bray, eds. "Resource Directory Description Language (RDDL) 2.0," January 2004

393 <http://www.openhealth.org/RDDL/20040118/rddl-20040118.html>

394 **[SecurityPolicy]**

395 G. Della-Libra, et. al. "Web Services Security Policy Language (WS-SecurityPolicy)", July 2005

396 <http://specs.xmlsoap.org/ws/2005/07/securitypolicy/ws-securitypolicy.pdf>

397 **[WS-Security]**

398 Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "OASIS Web Services Security:
399 SOAP Message Security 1.0 (WS-Security 2004)", OASIS Standard 200401, March 2004.

400 <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf>

401 Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "OASIS Web Services Security:
402 SOAP Message Security 1.1 (WS-Security 2004)", OASIS Standard 200602, February 2006.

403 [http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)

404 [spec-os-SOAPMessageSecurity.pdf](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)

Appendix A. Acknowledgments

This document is based on initial contribution to OASIS WS-RX Technical Committee by the following authors:

Stefan Batres-Editor(Microsoft), Ruslan Bilorusets(BEA), Don Box(Microsoft), Luis Felipe Cabrera(Microsoft), Derek Collison(TIBCO Software), Donald Ferguson(IBM), Christopher Ferris-Editor(IBM), Tom Freund(IBM), Mary Ann Hondo(IBM), John Ibbotson(IBM), Lei Jin(BEA), Chris Kaler(Microsoft), David Langworthy(Microsoft), Amelia Lewis(TIBCO Software), Rodney Limplecht(Microsoft), Steve Lucco(Microsoft), Don Mullen(TIBCO Software), Anthony Nadalin(IBM), Mark Nottingham(BEA), David Orchard(BEA), Shivajee Samdarshi(TIBCO Software), John Shewchuk(Microsoft), Tony Storey(IBM).

The following individuals have provided invaluable input into the initial contribution:

Keith Ballinger(Microsoft), Allen Brown(Microsoft), Michael Conner(IBM), Francisco Curbera(IBM), Steve Graham(IBM), Pat Helland(Microsoft), Rick Hill(Microsoft), Scott Hinkelman(IBM), Tim Holloway(IBM), Efim Hudis(Microsoft), Johannes Klein(Microsoft), Frank Leymann(IBM), Martin Nally(IBM), Peter Niblett(IBM), Jeffrey Schlimmer(Microsoft), Chris Sharp(IBM), James Snell(IBM), Keith Stobie(Microsoft), Satish Thatte(Microsoft), Stephen Todd(IBM), Sanjiva Weerawarana(IBM), Roger Wolter(Microsoft).

The following individuals were members of the committee during the development of this specification:

Abbie Barbir(Nortel), Charlton Barreto(Adobe), Stefan Batres(Microsoft), Hamid Ben Malek(Fujitsu), Andreas Bjarlestam(Ericsson), Toufic Boubrez(Layer 7), Doug Bunting(Sun), Lloyd Burch(Novell), Steve Carter(Novell), Martin Chapman(Oracle), Dave Chappell(Sonic), Paul Cotton(Microsoft), Glen Daniels(Sonic), Doug Davis(IBM), Blake Dournaee(Intel), Jacques Durand(Fujitsu), Colleen Evans(Microsoft), Christopher Ferris(IBM), Paul Fremantle(WSO2), Robert Freund(Hitachi), Peter Furniss(Erebor), Marc Goodner(Microsoft), Alastair Green(Choreology), Mike Grogan(Sun), Ondrej Hrebicek(Microsoft), Kazunori Iwasa(Fujitsu), Chamikara Jayalath(WSO2), Lei Jin(BEA), Ian Jones(BT plc), Anish Karmarkar(Oracle), Paul Knight(Nortel), Dan Leshchiner(Tibco), Mark Little(JBoss), Lily Liu(webMethods), Matt Lovett(IBM), Ashok Malhotra(Oracle), Jonathan Marsh(Microsoft), Daniel Millwood(IBM), Jeff Mischkinsky(Oracle), Nilo Mitra(Ericsson), Peter Niblett(IBM), Duane Nickull(Adobe), Eisaku Nishiyama(Hitachi), Dave Orchard(BEA), Chouthri Palanisamy(NEC), Sanjay Patil(SAP), Gilbert Pilz(BEA), Martin Raepplé(SAP), Eric Rajkovic(Oracle), Stefan Rossmanith(SAP), Tom Rutt(Fujitsu), Rich Salz(IBM), Shivajee Samdarshi(Tibco), Vladimir Videlov(SAP), Claus von Riegen(SAP), Pete Wenzel(Sun), Steve Winkler(SAP), Ümit Yalçınalp(SAP), Nobuyuki Yamamoto(Hitachi).

439 Appendix B. XML Schema

440 A normative copy of the XML Schema [XML-Schema Part1, XML-Schema Part2] description for this
441 specification may be retrieved from the following address:

442 [http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-schema-200702608/wsrmp-1.1-schema-](http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-schema-200702608/wsrmp-1.1-schema-200608.xsd)
443 [200608.xsd](http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-schema-200702608/wsrmp-1.1-schema-200608.xsd)

444 The following copy is provided for reference.

```
445 <?xml version="1.0" encoding="UTF-8"?>
446 <!--
447 OASIS takes no position regarding the validity or scope of any
448 intellectual property or other rights that might be claimed to pertain to
449 the implementation or use of the technology described in this document or
450 the extent to which any license under such rights might or might not be
451 available; neither does it represent that it has made any effort to
452 identify any such rights. Information on OASIS's procedures with respect
453 to rights in OASIS specifications can be found at the OASIS website.
454 Copies of claims of rights made available for publication and any
455 assurances of licenses to be made available, or the result of an attempt
456 made to obtain a general license or permission for the use of such
457 proprietary rights by implementors or users of this specification, can be
458 obtained from the OASIS Executive Director.
459 OASIS invites any interested party to bring to its attention any
460 copyrights, patents or patent applications, or other proprietary rights
461 which may cover technology that may be required to implement this
462 specification. Please address the information to the OASIS Executive
463 Director.
464 Copyright (c) OASIS Open 2002-2007. All Rights Reserved.
465 This document and translations of it may be copied and furnished to
466 others, and derivative works that comment on or otherwise explain it or
467 assist in its implementation may be prepared, copied, published and
468 distributed, in whole or in part, without restriction of any kind,
469 provided that the above copyright notice and this paragraph are included
470 on all such copies and derivative works. However, this document itself
471 does not be modified in any way, such as by removing the copyright notice
472 or references to OASIS, except as needed for the purpose of developing
473 OASIS specifications, in which case the procedures for copyrights defined
474 in the OASIS Intellectual Property Rights document must be followed, or
475 as required to translate it into languages other than English.
476 The limited permissions granted above are perpetual and will not be
477 revoked by OASIS or its successors or assigns.
478 This document and the information contained herein is provided on an "AS
479 IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED,
480 INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION
481 HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF
482 MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
483 -->
484 <xs:schema xmlns:tns="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
485 xmlns:xs="http://www.w3.org/2001/XMLSchema"
486 targetNamespace="http://docs.oasis-open.org/ws-rx/wsrmp/2007026. All-
487 Rights Reserved-
488 This document and translations of it may be copied and furnished to
489 others, and derivative works that comment on or otherwise explain it or
490 assist in its implementation may be prepared, copied, published and
491 distributed, in whole or in part, without restriction of any kind,
492 provided that the above copyright notice and this paragraph are included
493 on all such copies and derivative works. However, this document itself
494 does not be modified in any way, such as by removing the copyright notice
```

~~or references to OASIS, except as needed for the purpose of developing OASIS specifications, in which case the procedures for copyrights defined in the OASIS Intellectual Property Rights document must be followed, or as required to translate it into languages other than English. The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns. This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.~~

~~-->
 <xs:schema xmlns:tns="http://docs.oasis-open.org/ws-rx/wsrmp/200608"
 xmlns:xs="http://www.w3.org/2001/XMLSchema"
 targetNamespace="http://docs.oasis-open.org/ws-rx/wsrmp/200608"
 elementFormDefault="qualified" attributeFormDefault="unqualified">
 <xs:element name="RMAssertion">
 <xs:complexType>
 <xs:sequence>
 <xs:any namespace="##other" processContents="lax" minOccurs="0"
 maxOccurs
 </xs:sequence>
 <xs:anyAttribute namespace="##any" processContents="lax"/>
 </xs:complexType>
 </xs:element>
 <xs:element name="SequenceSTR">
 <xs:complexType>
 <xs:sequence/>
 <xs:anyAttribute namespace="##any" processContents="lax"/>
 </xs:complexType>
 </xs:element>
 <xs:element name="SequenceTransportSecurity">
 <xs:complexType>
 <xs:sequence/>
 <xs:anyAttribute namespace="##any" processContents="lax"/>
 </xs:complexType>
 </xs:element>
 </xs:schema>~~

<xs:element name="DeliveryAssurance">
 <xs:complexType>
 <xs:sequence>
 <xs:any namespace="##any" processContents="lax" minOccurs="0"
 maxOccurs="unbounded"/>
 </xs:sequence>
 </xs:complexType>
 </xs:element>
 <xs:element name="ExactlyOnce">
 <xs:complexType>
 <xs:sequence/>
 </xs:complexType>
 </xs:element>
 <xs:element name="AtLeastOnce">
 <xs:complexType>
 <xs:sequence/>
 </xs:complexType>
 </xs:element>
 <xs:element name="AtMostOnce">
 <xs:complexType>
 <xs:sequence/>
 </xs:complexType>
 </xs:element>


```
556 <xs:element name="InOrder">
557   <xs:complexType>
558     <xs:sequence/>
559   </xs:complexType>
560 </xs:element>
561 </xs:schema>
```

562 Appendix C. Revision History

Revision	Date	By Whom	What
wd-01.doc	2005-07-06	Ümit Yalçinalp	Initial version created based on submission by the authors.
1.0-wd-01.swx	2005-09-01	Ümit Yalçinalp	Reformatted using Open Office
1.1-wd-01.swx	2005-09-18	Ümit Yalçinalp	Applied resolution i001 Applied resolution i015/16 (doc identifier) Partial application of i017, final yyyy/mm required, changed doc URI to TBD pending yyyy/mm Deleted original copyright section
1.1-wd-01.swx	2005-10-02	Anish Karmarkar	Applied resolution of i013 + minor editorial changes + fixed resolution of i017
1.1-wd-01.swx	2005-10-04	Ümit Yalçinalp	Applied actual value for yyyy/mm. Added resolution of i009
1.1-wd-01.swx	2005-10-06	Ümit Yalçinalp	Editorial fixes suggested by Anish Updated wd draft date to October 6th
1.1-wd-01.swx	2005-10-19	Ümit Yalçinalp	Editorial change to remove .swx suffix from doc id
wd-02	2005-11-03	Gilbert Pilz	Start wd-02 by changing title page from cd-01.
wd-02	2005-11-30	Gilbert Pilz	i072 – editorial nits
wd-02	2005-11-30	Gilbert Pilz	i074 - Use of [tcShortName] in artifact locations namespaces, etc
wd-02	2005-12-01	Gilbert Pilz	Updated fix to i074 to remove trailing '/' from wsrmp namespace.
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i022
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i024
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i054
wd-02	2005-12-01	Anish Karmarkar	Applied resolution of i073
wd-2	2005-12-05	Anish Karmarkar	Applied resolution of i055
wd-2	2005-12-05	Ümit Yalçinalp	Changed fixed date in footer to current date
wd-3	2005-12-21	Doug Davis	Added i050
wd-3	2005-12-23	Ümit Yalçinalp	i057 resolution
wd-3	2005-12-23	Ümit Yalçinalp	Changed the ref to WS-RM to the WS-RX committee.

Revision	Date	By Whom	What
			draft instead of original version Fixed Dug's email address
wd-3	2005-12-23	Ümit Yalçınalp	I060 resolution
wd-03	2005-12-27	Gilbert Pilz	Remove schema example and put it in its own artifact (wsrmp-1.1-schema-200510.xsd). Convert source file to OpenDocument format. Make line numbers all the same style.
wd-03	2005-12-28	Anish Karmarkar	Included a section link to c:\temp\wsrmp-1.1-schema-200510.xsd
wd-03	2006-01-04	Gilbert Pilz	Fixed formatting of included section.
wd-03	2006-01-05	Gilbert Pilz	Fix closing tag of normative outline for RMAssertion.
wd-04	2006-11-11	Doug Davis	Minor tweaks/typos
wd-05	2006-01-23	Gilbert Pilz	Start wd-05 by accepting all changes from wd-04
wd-06	2006-01-23	Doug Davis	Minor typos found by Marc
wd-06	2006-02-14	Doug Davis	Issue 075 resolution
wd-06	2006-02-14	Doug Davis	Issues 086, 087 resolutions
wd-06	2006-02-15	Gilbert Pilz	Issue 088; added link for namespace URI; added text describing link; added non-normative reference for RDDL 2.0
wd-06	2006-02-17	Anish Karmarkar	Removed a sentence in section 2.1 that talked about RM assertion parameters, as there aren't any.
wd-06	2006-02-17	Anish Karmarkar	Change the namespace to 200602.
wd-07	2006-02-22	Doug Davis	Accept all changes to create new WD Minor typo fixed – thanks to Paul Cotton
wd-07	2006-02-23	Doug Davis	Added missing namespace table entries - MarcG
wd-07	2006-03-08	Doug Davis	Issue 097 applied
wd-08	2006-04-11	Doug Davis	Issue 021 applied
wd-08	2006-04-24	Gilbert Pilz	Misc cleanups prior to publishing to TC.
wd-09	2006-05-29	Gilbert Pilz	Issue 117 applied
wd-10	2006-06-05	Gilbert Pilz	Accept all changes; bump WD number
wd-10	2006-06-07	Doug Davis	Applied lots of minor edits from Marc Goodner
wd-10	2006-06-13	Doug Davis	Applied a couple of minor edits
wd-10	2006-07-21	Doug Davis	Issues 122-124 applied

Revision	Date	By Whom	What
wd-10	2006-07-27	Doug Davis	Copied list of TC members from RM spec (i134)
wd-10	2006-08-04	Doug Davis	Updated old namespaces – found by PaulC
wd-10	2006-08-04	Doug Davis	Verify all [refs]
wd-10	2006-08-04	Doug Davis	Change namespace to 2006/08
cd-04	2006-08-11	Doug Davis	Issue 158 applied
cd-04	2006-08-16	Gilbert Pilz	Fix date at 08/11/2006; formatting changes for better HTML rendering.
wd-11	2006-10-25	Doug Davis	Accept all changes, update to wd11
wd-11	2006-10-26	Doug Davis	PR004 applied
wd-11	2007-01-26	Doug Davis	PR037 applied
wd-12	2007-01-31	Doug Davis	Lots of typos from MarcG Updated WD number and date
wd-12	2007-02-01	Doug Davis	PR035 (009.020 dups) applied
Revision	Date	By Whom	What
wd-01.doc	2005-07-06	Ümit Yalçınalp	Initial version created based on submission by the authors.
1.0-wd-01.swx	2005-09-01	Ümit Yalçınalp	Reformatted using Open Office
1.1-wd-01.swx	2005-09-18	Ümit Yalçınalp	Applied resolution i001 Applied resolution i015/16 (doc identifier) Partial application of i017, final yyyy/mm required, changed doc URI to TBD pending yyyy/mm Deleted original copyright section
1.1-wd-01.swx	2005-10-02	Anish Karmarkar	Applied resolution of i013 + minor editorial changes + fixed resolution of i017
1.1-wd-01.swx	2005-10-04	Ümit Yalçınalp	Applied actual value for yyyy/mm. Added resolution of i009
1.1-wd-01.swx	2005-10-06	Ümit Yalçınalp	Editorial fixes suggested by Anish Updated wd draft date to October 6th
1.1-wd-01.swx	2005-10-19	Ümit Yalçınalp	Editorial change to remove .swx suffix from doc id
wd-02	2005-11-03	Gilbert Pilz	Start wd-02 by changing title page from cd-01.
wd-02	2005-11-30	Gilbert Pilz	i072 — editorial nits
wd-02	2005-11-30	Gilbert Pilz	i074 — Use of [teShortName] in artifact locations namespaces, etc

Revision	Date	By Whom	What
wd-02	2005-12-01	Gilbert Pilz	Updated fix to i074 to remove trailing '/' from wsrmp-namespace.
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i022
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i024
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i054
wd-02	2005-12-01	Anish Karmarkar	Applied resolution of i073
wd-2	2005-12-05	Anish Karmarkar	Applied resolution of i055
wd-2	2005-12-05	Ümit Yalçınalp	Changed fixed date in footer to current date
wd-3	2005-12-21	Doug Davis	Added i050
wd-3	2005-12-23	Ümit Yalçınalp	i057 resolution
wd-3	2005-12-23	Ümit Yalçınalp	Changed the ref to WS-RM to the WS-RX committee draft instead of original version Fixed Dug's email address
wd-3	2005-12-23	Ümit Yalçınalp	i060 resolution
wd-03	2005-12-27	Gilbert Pilz	Remove schema example and put it in its own artifact (wsrmp-1.1-schema-200510.xsd). Convert source file to OpenDocument format. Make line numbers all the same style.
wd-03	2005-12-28	Anish Karmarkar	Included a section link to c:\temp\wsrmp-1.1-schema-200510.xsd
wd-03	2006-01-04	Gilbert Pilz	Fixed formatting of included section.
wd-03	2006-01-05	Gilbert Pilz	Fix closing tag of normative outline for RMAssertion.
wd-04	2006-11-11	Doug Davis	Minor tweaks/types
wd-05	2006-01-23	Gilbert Pilz	Start wd-05 by accepting all changes from wd-04
wd-06	2006-01-23	Doug Davis	Minor typos found by Mare
wd-06	2006-02-14	Doug Davis	Issue 075 resolution
wd-06	2006-02-14	Doug Davis	Issues 086, 087 resolutions
wd-06	2006-02-15	Gilbert Pilz	Issue 088; added link for namespace URI; added text describing link; added non-normative reference for RDDL 2.0
wd-06	2006-02-17	Anish Karmarkar	Removed a sentence in section 2.1 that talked about RM assertion parameters, as there aren't any.
wd-06	2006-02-17	Anish Karmarkar	Change the namespace to 200602.
wd-07	2006-02-22	Doug Davis	Accept all changes to create new WD

Revision	Date	By Whom	What
			Minor typo fixed—thanks to Paul Cotton
wd-07	2006-02-23	Doug Davis	Added missing namespace table entries—MarcG
wd-07	2006-03-08	Doug Davis	Issue 097 applied
wd-08	2006-04-11	Doug Davis	Issue 021 applied
wd-08	2006-04-24	Gilbert Pilz	Misc cleanups prior to publishing to TC.
wd-09	2006-05-29	Gilbert Pilz	Issue 117 applied
wd-10	2006-06-05	Gilbert Pilz	Accept all changes; bump WD number
wd-10	2006-06-07	Doug Davis	Applied lots of minor edits from Marc Goodner
wd-10	2006-06-13	Doug Davis	Applied a couple of minor edits
wd-10	2006-07-21	Doug Davis	Issues 122-124 applied
wd-10	2006-07-27	Doug Davis	Copied list of TC members from RM spec (i134)
wd-10	2006-08-04	Doug Davis	Updated old namespaces—found by PaulG
wd-10	2006-08-04	Doug Davis	Verify all [refs]
wd-10	2006-08-04	Doug Davis	Change namespace to 2006/08
ed-04	2006-08-11	Doug Davis	Issue 158 applied
ed-04	2006-08-16	Gilbert Pilz	Fix date at 08/11/2006; formatting changes for better HTML rendering.

563 **Appendix D. Notices**

564 OASIS takes no position regarding the validity or scope of any intellectual property or other rights that
565 might be claimed to pertain to the implementation or use of the technology described in this document or
566 the extent to which any license under such rights might or might not be available; neither does it represent
567 that it has made any effort to identify any such rights. Information on OASIS's procedures with respect to
568 rights in OASIS specifications can be found at the OASIS website. Copies of claims of rights made
569 available for publication and any assurances of licenses to be made available, or the result of an attempt
570 made to obtain a general license or permission for the use of such proprietary rights by implementors or
571 users of this specification, can be obtained from the OASIS Executive Director.

572 OASIS invites any interested party to bring to its attention any copyrights, patents or patent applications, or
573 other proprietary rights which may cover technology that may be required to implement this specification.
574 Please address the information to the OASIS Executive Director.

575 Copyright (C) OASIS Open (2007~~6~~). All Rights Reserved.

576 This document and translations of it may be copied and furnished to others, and derivative works that
577 comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and
578 distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and
579 this paragraph are included on all such copies and derivative works. However, this document itself may
580 not be modified in any way, such as by removing the copyright notice or references to OASIS, except as
581 needed for the purpose of developing OASIS specifications, in which case the procedures for copyrights
582 defined in the OASIS Intellectual Property Rights document must be followed, or as required to translate it
583 into languages other than English.

584 The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors
585 or assigns.

586 This document and the information contained herein is provided on an "AS IS" basis and OASIS
587 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY
588 WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR
589 ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.