



# Web Services ReliableMessaging Policy Assertion (WS-RM Policy) 1.1

## Committee Draft 05

1 February 2007

### Specification URIs:

#### This Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.html>

#### Previous Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200608/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200608/wsrmp-1.1-spec-cd-05.html>

#### Latest Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702>

#### Latest Approved Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.html>

### Technical Committee:

OASIS Web Services Reliable Exchange (WS-RX) TC

### Chairs:

Paul Fremantle <[paul@wso2.com](mailto:paul@wso2.com)>

Sanjay Patil <[sanjay.patil@sap.com](mailto:sanjay.patil@sap.com)>

### Editors:

Doug Davis, IBM <[dug@us.ibm.com](mailto:dug@us.ibm.com)>

Anish Karmarkar, Oracle <[Anish.Karmarkar@oracle.com](mailto:Anish.Karmarkar@oracle.com)>

Gilbert Pilz, BEA <[gpilz@bea.com](mailto:gpilz@bea.com)>

Ümit Yalçinalp, SAP <[umit.yalcinalp@sap.com](mailto:umit.yalcinalp@sap.com)>

### Related Work:

This specification replaces or supercedes:

- WS-ReliableMessaging Policy v1.0

### Declared XML Namespaces:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702>

### Abstract:

This specification describes a domain-specific policy assertion for WS-ReliableMessaging [WS-RM] that can be specified within a policy alternative as defined in WS-Policy Framework [WS-Policy].

By using the XML [XML], SOAP [SOAP 1.1], [SOAP 1.2] and WSDL [WSDL 1.1] extensibility

models, the WS\* specifications are designed to be composed with each other to provide a rich Web services environment. This by itself does not provide a negotiation solution for Web services. This is a building block that is used in conjunction with other Web service and application-specific protocols to accommodate a wide variety of policy exchange models.

**Status:**

This document was last revised or approved by the WS-RX on the above date. The level of approval is also listed above. Check the "Latest Version" or "Latest Approved Version" location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <http://www.oasis-open.org/committees/ws-rx>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/ws-rx/ipr.php>).

The non-normative errata page for this specification is located at <http://www.oasis-open.org/committees/ws-rx>.

## 55 Notices

56 Copyright © OASIS® 1993–2007. All Rights Reserved. OASIS trademark, IPR and other policies apply.

57 All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual  
58 Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

59 This document and translations of it may be copied and furnished to others, and derivative works that  
60 comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and  
61 distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and  
62 this section are included on all such copies and derivative works. However, this document itself may not be  
63 modified in any way, including by removing the copyright notice or references to OASIS, except as needed  
64 for the purpose of developing any document or deliverable produced by an OASIS Technical Committee  
65 (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or  
66 as required to translate it into languages other than English.

67 The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors  
68 or assigns.

69 This document and the information contained herein is provided on an "AS IS" basis and OASIS  
70 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY  
71 WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY  
72 OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A  
73 PARTICULAR PURPOSE.

74 OASIS requests that any OASIS Party or any other party that believes it has patent claims that would  
75 necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to  
76 notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such  
77 patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced  
78 this specification.

79 OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any  
80 patent claims that would necessarily be infringed by implementations of this specification by a patent  
81 holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR  
82 Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims  
83 on its website, but disclaims any obligation to do so.

84 OASIS takes no position regarding the validity or scope of any intellectual property or other rights that  
85 might be claimed to pertain to the implementation or use of the technology described in this document or  
86 the extent to which any license under such rights might or might not be available; neither does it represent  
87 that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to  
88 rights in any document or deliverable produced by an OASIS Technical Committee can be found on the  
89 OASIS website. Copies of claims of rights made available for publication and any assurances of licenses  
90 to be made available, or the result of an attempt made to obtain a general license or permission for the use  
91 of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS  
92 Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any  
93 information or list of intellectual property rights will at any time be complete, or that any claims in such list  
94 are, in fact, Essential Claims.

95 The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be  
96 used only to refer to the organization and its official outputs. OASIS welcomes reference to, and

97 implementation and use of, specifications, while reserving the right to enforce its marks against misleading  
98 uses. Please see <http://www.oasis-open.org/who/trademark.php> for above guidance.

## 99 **Table of Contents**

100	<b>1</b>	<b>Introduction.....</b>	<b>6</b>
101	1.1	Goals and Requirements .....	6
102	1.1	Terminology .....	6
103	1.2	Namespace.....	7
104	1.3	Compliance.....	7
105	<b>2</b>	<b>RM Policy Assertions.....</b>	<b>8</b>
106	2.1	Assertion Model .....	8
107	2.2	Normative Outline .....	8
108	2.3	Assertion Attachment.....	9
109	2.4	Assertion Example.....	11
110	2.5	Sequence Security Policy .....	11
111	<b>3</b>	<b>Security Considerations .....</b>	<b>13</b>
112	<b>4</b>	<b>References .....</b>	<b>14</b>
113	4.1	Normative.....	14
114	4.2	Non Normative.....	15
115		<b>Appendix A. Acknowledgments .....</b>	<b>16</b>
116		<b>Appendix B. XML Schema.....</b>	<b>17</b>
117		<b>Appendix C. Revision History.....</b>	<b>19</b>

# 1 Introduction

This specification defines a domain-specific policy assertion for reliable messaging for use with WS-Policy and WS-ReliableMessaging.

## 1.1 Goals and Requirements

### 1.1.1 Requirements

### 1.1 Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [KEYWORDS].

This specification uses the following syntax to define normative outlines for messages:

- The syntax appears as an XML instance, but values in italics indicate data types instead of values.
- Characters are appended to elements and attributes to indicate cardinality:
  - "?" (0 or 1)
  - "\*" (0 or more)
  - "+" (1 or more)
- The character "|" is used to indicate a choice between alternatives.
- The characters "[" and "]" are used to indicate that contained items are to be treated as a group with respect to cardinality or choice.
- An ellipsis (i.e. "...") indicates a point of extensibility that allows other child, or attribute, content. Additional children and/or attributes MAY be added at the indicated extension points but MUST NOT contradict the semantics of the parent and/or owner, respectively. If an extension is not recognized it SHOULD be ignored.
- XML namespace prefixes (See Section 1.3) are used to indicate the namespace of the element being defined.

Elements and Attributes defined by this specification are referred to in the text of this document using XPath 1.0 [XPATH 1.0] expressions. Extensibility points are referred to using an extended version of this syntax:

- An element extensibility point is referred to using {any} in place of the element name. This indicates that any element name can be used, from any namespace other than the wsrn: namespace.
- An attribute extensibility point is referred to using @{any} in place of the attribute name. This indicates that any attribute name can be used, from any namespace other than the wsrn: namespace.

## 1.2 Namespace

The XML namespace [XML-ns] URI that MUST be used by implementations of this specification is:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702>

Dereferencing the above URI will produce the Resource Directory Description Language [RDDL 2.0] document that describes this namespace.

Table 1 lists the XML namespaces that are used in this specification. The choice of any namespace prefix is arbitrary and not semantically significant.

Table 1

Prefix	Namespace	Specification
wsdl	<a href="http://schemas.xmlsoap.org/wsdl/">http://schemas.xmlsoap.org/wsdl/</a>	[WSDL 1.1]
wsp	<a href="http://schemas.xmlsoap.org/ws/2004/09/policy">http://schemas.xmlsoap.org/ws/2004/09/policy</a>	[WS-Policy]
wsrmp	<a href="http://docs.oasis-open.org/ws-rx/wsrmp/200702">http://docs.oasis-open.org/ws-rx/wsrmp/200702</a>	This specification.
wsu	<a href="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd</a>	WS-Security-Utility Schema

## 1.3 Compliance

An implementation is not compliant with this specification if it fails to satisfy one or more of the MUST or REQUIRED level requirements defined herein. A SOAP Node MUST NOT use the XML namespace identifier for this specification (listed in Section 1.3) within SOAP Envelopes unless it is compliant with this specification.

Normative text within this specification takes precedence over normative outlines, which in turn take precedence over the XML Schema [XML-Schema Part1, XML-Schema Part2] descriptions.

## 2 RM Policy Assertions

WS-Policy Framework and WS-Policy Attachment [WS-PolicyAttachment] collectively define a framework, model and grammar for expressing the requirements, and general characteristics of entities in an XML Web services-based system. To enable an RM Destination and an RM Source to describe their requirements for a given Sequence, this specification defines a single RM policy assertion that leverages the WS-Policy framework.

### 2.1 Assertion Model

The RM policy assertion indicates that the RM Source and RM Destination MUST use WS-ReliableMessaging to ensure reliable delivery of messages. Specifically, the WS-ReliableMessaging protocol determines invariants maintained by the reliable messaging endpoints and the directives used to track and manage the delivery of a Sequence of messages.

### 2.2 Normative Outline

The normative outline for the RM assertion is:

```
<wsrmp:RMAssertion [wsp:Optional="true"]? ... >
  <wsp:Policy>
    [ <wsrmp:SequenceSTR/> |
      <wsrmp:SequenceTransportSecurity/> ] ?
    <wsrmp:DeliveryAssurance>
      <wsp:Policy>
        [ <wsrmp:ExactlyOnce/> |
          <wsrmp:AtLeastOnce/> |
          <wsrmp:AtMostOnce/> ]
        <wsrmp:InOrder/> ?
      </wsp:Policy>
    </wsrmp:DeliveryAssurance> ?
  </wsp:Policy>
  ...
</wsrmp:RMAssertion>
```

The following describes the content model of the RMAssertion element.

/wsrmp:RMAssertion

A policy assertion that specifies that WS-ReliableMessaging protocol MUST be used when sending messages.

/wsrmp:RMAssertion/@wsp:Optional="true"

Per WS-Policy, this is compact notation for two policy alternatives, one with and one without the assertion. The intuition is that the behavior indicated by the assertion is optional, or in this case, that WS-ReliableMessaging MAY be used.

/wsrmp:RMAssertion/wsp:Policy

This required element allows for the inclusion of nested policy assertions.

/wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceSTR

When present, this assertion defines the requirement that an RM Sequence MUST be bound to an explicit token that is referenced from a wsse:SecurityTokenReference in the CreateSequence message. See section 2.5.1.



208 /wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceTransportSecurity

209 When present, this assertion defines the requirement that an RM Sequence MUST be bound to

210 the session(s) of the underlying transport-level protocol used to carry the `CreateSequence` and

211 `CreateSequenceResponse` message. When present, this assertion MUST be used in

212 conjunction with the `sp:TransportBinding` assertion, see section 2.5.2.

213 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance

214 This expression, which may be omitted, describes the message delivery quality of service between

215 the RM and application layer. When used by an RM Destination it expresses the delivery

216 assurance in effect between the RM Destination and its corresponding application destination, and

217 it also indicates requirements on any RM Source that transmits messages to this RM destination.

218 Conversely when used by an RM Source it expresses the delivery assurance in effect between the

219 RM Source and its corresponding application source, as well as indicating requirements on any

220 RM Destination that receives messages from this RM Source. In either case the delivery

221 assurance does not affect the messages transmitted on the wire. Absence of this expression from

222 a `wsrmp:RMAssertion` policy assertion simply means that the endpoint has chosen not to

223 advertise its delivery assurance characteristics.

224 Note that when there are multiple policy alternatives of the RM Assertion, the Delivery Assurance

225 on each MUST NOT conflict.

226 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy

227 This required element identifies additional requirements for the use of the

228 `wsrmp:DeliveryAssurance`.

229 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:ExactlyOnce

230 This expresses the ExactlyOnce Delivery Assurance defined in [].

231 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtLeastOnce

232 This expresses the AtLeastOnce Delivery Assurance defined in [].

233 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtMostOnce

234 This expresses the AtMostOnce Delivery Assurance defined in [].

235 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:InOrder

236 This expresses the InOrder Delivery Assurance defined in [].

237 /wsrmp:RMAssertion/{any}

238 This is an extensibility mechanism to allow different (extensible) types of information, based on a

239 schema, to be passed.

240 /wsrmp:RMAssertion/@{any}

241 This is an extensibility mechanism to allow different (extensible) types of information, based on a

242 schema, to be passed.

## 243 2.3 Assertion Attachment

244 The RM policy assertion is allowed to have the following Policy Subjects [[WS-PolicyAttachment](#)]:

- 245 • Endpoint Policy Subject
- 246 • Message Policy Subject

247 WS-PolicyAttachment defines a set of WSDL/1.1 policy attachment points for each of the above Policy

248 Subjects. Since an RM policy assertion specifies a concrete behavior, it MUST NOT be attached to the  
249 abstract WSDL policy attachment points.

250 The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an  
251 RM policy assertion but which MUST NOT have RM policy assertions attached:

- 252     • wsdl:message
- 253     • wsdl:portType/wsdl:operation/wsdl:input
- 254     • wsdl:portType/wsdl:operation/wsdl:output
- 255     • wsdl:portType/wsdl:operation/wsdl:fault
- 256     • wsdl:portType

257 The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an  
258 RM policy assertion and which MAY have RM policy assertions attached:

- 259     • wsdl:port
- 260     • wsdl:binding
- 261     • wsdl:binding/wsdl:operation/wsdl:input
- 262     • wsdl:binding/wsdl:operation/wsdl:output
- 263     • wsdl:binding/wsdl:operation/wsdl:fault

264 If an RM policy assertion is attached to any of:

- 265     • wsdl:binding/wsdl:operation/wsdl:input
- 266     • wsdl:binding/wsdl:operation/wsdl:output
- 267     • wsdl:binding/wsdl:operation/wsdl:fault

268 then an RM policy assertion, specifying wsp:Optional=true MUST be attached to the corresponding  
269 wsdl:binding or wsdl:port, indicating that the endpoint supports WS-RM. Any messages, regardless of  
270 whether they have an attached Message Policy Subject RM policy assertion, MAY be sent to that endpoint  
271 using WS-RM. Additionally, the receiving endpoint MUST NOT reject any message belonging to a  
272 Sequence, simply because there was no Message Policy Subject RM policy assertion attached to that  
273 message. There might be certain RM implementations that are incapable of applying RM Quality of  
274 Service (QoS) semantics on a per-message basis. In order to ensure the broadest interoperability, when  
275 an endpoint decorates its WSDL with RM policy assertions using Message Policy Subject, it MUST also be  
276 prepared to accept that all messages sent to that endpoint might be sent within the context of an RM  
277 Sequence, regardless of whether the corresponding wsdl:input, wsdl:output or wsdl:fault had an attached  
278 RM policy assertion.

279 Rather than turn away messages that were unnecessarily sent with RM semantics, the receiving endpoint  
280 described by the WSDL MUST accept these messages.

281 By attaching an RM policy assertion that specifies wsp:Optional="true" to the corresponding endpoint that  
282 has attached RM policy assertions at the Message Policy Subject level, the endpoint is describing the  
283 above constraint in policy.

284 In the case where an optional RM Assertion applies to an output message, there is no requirement on the  
285 client to support an RM Destination implementation

## 2.4 Assertion Example

Table 2 lists an example use of the RM policy assertion.

Table 2: Example policy with RM policy assertion

```
(01)<wsdl:definitions
(02)   targetNamespace="example.com"
(03)   xmlns:tns="example.com"
(04)   xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
(05)   xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
(06)   xmlns:wsrmp="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
(07)   xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-
wss-wssecurity-utility-1.0.xsd">
(08)
(09)   <wsp:UsingPolicy wsdl:required="true" />
(10)
(11)   <wsp:Policy wsu:Id="MyPolicy" >
(12)     <wsrmp:RMAssertion>
(13)       <wsp:Policy/>
(14)     </wsrmp:RMAssertion>
(15)     <!-- omitted assertions -->
(16)   </wsp:Policy>
(17)
(18)   <!-- omitted elements -->
(19)
(20)   <wsdl:binding name="MyBinding" type="tns:MyPortType" >
(21)     <wsp:PolicyReference URI="#MyPolicy" />
(22)     <!-- omitted elements -->
(23)   </wsdl:binding>
(24)
(25)</wsdl:definitions>
```

Line (09) in Table 2 indicates that WS-Policy is in use as a required extension.

Lines (11-16) are a policy expression that includes a RM policy assertion (lines 12-14) to indicate that WS-ReliableMessaging must be used.

Lines (20-23) are a WSDL binding. Line (21) indicates that the policy in lines (11-16) applies to this binding, specifically indicating that WS-ReliableMessaging must be used over all the messages in the binding.

## 2.5 Sequence Security Policy

WS-SecurityPolicy [SecurityPolicy] provides a framework and grammar for expressing the security requirements and characteristics of entities in a XML web services based system. The following assertions MAY be used in conjunction with WS-SecurityPolicy to express additional security requirements particular to RM Sequences.

### 2.5.1 RM Assertion with Sequence STR Assertion

This version of the RM assertion includes the requirement that an RM Sequence MUST be bound to an explicit token that is referenced from a `wsse:SecurityTokenReference` in the `CreateSequence` message.

This assertion MUST apply to [Endpoint Policy Subject]. The normative outline for this form of the Sequence STR Assertion is:

```

332 <wsrmp:RMAssertion [wsp:Optional="true"]? ...>
333   <wsp:Policy>
334     <wsrmp:SequenceSTR/>
335     <wsp:Policy>
336   </wsrmp:RMAssertion>

```

The following describes the content model of the `SequenceSTR` element.

`/wsrmp:SequenceSTR`

A policy assertion that specifies security requirements which **MUST** be used with an RM Sequence that are particular to WS-RM and beyond what can be expressed in WS-SecurityPolicy.

## 2.5.2 RM Assertion with Sequence Transport Security Assertion

This version of the RM assertion includes the requirement that an RM Sequence **MUST** be bound to the session(s) of the underlying transport-level security protocol (e.g. SSL/TLS) used to carry the `CreateSequence` and `CreateSequenceResponse` messages.

This assertion **MUST** apply to [Endpoint Policy Subject]. This assertion **MUST** be used in conjunction with the `sp:TransportBinding` assertion that requires the use of some transport-level security mechanism (e.g. `sp:HttpsToken`).

The normative outline for this form of the RM Assertion with the Sequence Transport Security Assertion is:

```

349 <wsp:Policy>
350   <wsp:ExactlyOne>
351     <wsp:All>
352       <wsrm:RMAssertion [wsp:Optional="true"]> ...>
353       <wsp:Policy>
354         <wsrmp:SequenceTransportSecurity/>
355       </wsp:Policy>
356     </wsrm:RMAssertion>
357     <sp:TransportBinding ...>
358     ...
359   </sp:TransportBinding>
360   <wsp:All>
361     <wsp:ExactlyOne>
362   </wsp:Policy>

```

The following describes the content model of the `SequenceTransportSecurity` element.

`/wsrmp:SequenceTransportSecurity`

A policy assertion that specifies that any Sequences targeted to the indicated endpoint **MUST** be bound to the underlying session(s) of the transport-level security used to carry messages related to the Sequence.

This form of the RM Assertion says that an endpoint **MAY** have RM as an option but always requires HTTPS to be used. All the `SequenceTransportSecurity` assertion indicates is that RM's rules for protecting the Sequence over TLS are followed.

### 3 Security Considerations

It is strongly RECOMMENDED that policies and assertions be signed to prevent tampering.

It is RECOMMENDED that policies SHOULD NOT be accepted unless they are signed and have an associated security token to specify the signer has proper claims for the given policy. That is, a relying party shouldn't rely on a policy unless the policy is signed and presented with sufficient claims to pass the relying parties acceptance criteria.

It should be noted that the mechanisms described in this document could be secured as part of a SOAP message using WS-Security [[WS-Security](#)] or embedded within other objects using object-specific security mechanisms.

## 4 References

### 4.1 Normative

#### [KEYWORDS]

S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," RFC 2119, Harvard University, March 1997.

<http://www.ietf.org/rfc/rfc2119.txt>

#### [SOAP 1.1]

W3C Note, "SOAP: Simple Object Access Protocol 1.1" 08 May 2000.

<http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

#### [SOAP 1.2]

W3C Recommendation, "SOAP Version 1.2 Part 1: Messaging Framework" June 2003.

<http://www.w3.org/TR/2003/REC-soap12-part1-20030624/>

#### [URI]

T. Berners-Lee, R. Fielding, L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax," RFC 3986, MIT/LCS, U.C. Irvine, Xerox Corporation, January 2005.

<http://ietf.org/rfc/rfc3986>

#### [WS-RM]

OASIS WS-RX Technical Committee Draft, "Web Services Reliable Messaging (WS-ReliableMessaging)," August 2005.

<http://docs.oasis-open.org/ws-rx/wsrp/200702/wsrp-1.1-spec-cd-05.pdf>

#### [WS-Policy]

W3C Member Submission, "Web Services Policy Framework (WS-Policy)," April 2006.

<http://www.w3.org/Submission/2006/SUBM-WS-Policy-20060425/>

#### [WS-PolicyAttachment]

W3C Member Submission, "Web Services Policy Attachment (WS-PolicyAttachment)," April 2006.

<http://www.w3.org/Submission/2006/SUBM-WS-PolicyAttachment-20060425/>

#### [WSDL 1.1]

W3C Note, "Web Services Description Language (WSDL 1.1)," 15 March 2001.

<http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

#### [XML]

W3C Recommendation, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", September 2006.

<http://www.w3.org/TR/REC-xml/>

#### [XML-ns]

W3C Recommendation, "Namespaces in XML," 14 January 1999.

414 <http://www.w3.org/TR/1999/REC-xml-names-19990114/>

415 **[XML-Schema Part1]**

416 W3C Recommendation, "XML Schema Part 1: Structures," October 2004.

417 <http://www.w3.org/TR/xmlschema-1/>

418 **[XML-Schema Part2]**

419 W3C Recommendation, "XML Schema Part 2: Datatypes," October 2004.

420 <http://www.w3.org/TR/xmlschema-2/>

421 **[XPath 1.0]**

422 W3C Recommendation, "XML Path Language (XPath) Version 1.0," 16 November 1999.

423 <http://www.w3.org/TR/xpath>

424 **4.2 Non Normative**

425 **[RDDL 2.0]**

426 Jonathan Borden, Tim Bray, eds. "Resource Directory Description Language (RDDL) 2.0," January 2004

427 <http://www.openhealth.org/RDDL/20040118/rddl-20040118.html>

428 **[SecurityPolicy]**

429 G. Della-Libra, et. al. "Web Services Security Policy Language (WS-SecurityPolicy)", July 2005

430 <http://specs.xmlsoap.org/ws/2005/07/securitypolicy/ws-securitypolicy.pdf>

431 **[WS-Security]**

432 Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "OASIS Web Services Security:  
433 SOAP Message Security 1.0 (WS-Security 2004)", OASIS Standard 200401, March 2004.

434 <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf>

435 Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "OASIS Web Services Security:  
436 SOAP Message Security 1.1 (WS-Security 2004)", OASIS Standard 200602, February 2006.

437 [http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)

438 [SOAPMessageSecurity.pdf](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)

## 439 **Appendix A. Acknowledgments**

440 This document is based on initial contribution to OASIS WS-RX Technical Committee by the following  
441 authors:

442 Stefan Batres-Editor(Microsoft), Ruslan Bilorusets(BEA), Don Box(Microsoft), Luis Felipe  
443 Cabrera(Microsoft), Derek Collison(TIBCO Software), Donald Ferguson(IBM), Christopher  
444 Ferris(IBM), Tom Freund(IBM), Mary Ann Hondo(IBM), John Ibbotson(IBM), Lei Jin(BEA), Chris  
445 Kaler(Microsoft), David Langworthy(Microsoft), Amelia Lewis(TIBCO Software), Rodney  
446 Limprecht(Microsoft), Steve Lucco(Microsoft), Don Mullen(TIBCO Software), Anthony  
447 Nadalin(IBM), Mark Nottingham(BEA), David Orchard(BEA), Shivajee Samdarshi(TIBCO  
448 Software), John Shewchuk(Microsoft), Tony Storey(IBM).

449 The following individuals have provided invaluable input into the initial contribution:

450 Keith Ballinger(Microsoft), Allen Brown(Microsoft), Michael Conner(IBM), Francisco Curbera(IBM),  
451 Steve Graham(IBM), Pat Helland(Microsoft), Rick Hill(Microsoft), Scott Hinkelman(IBM), Tim  
452 Holloway(IBM), Efim Hudis(Microsoft), Johannes Klein(Microsoft), Frank Leymann(IBM), Martin  
453 Nally(IBM), Peter Niblett(IBM), Jeffrey Schlimmer(Microsoft), Chris Sharp(IBM), James Snell(IBM),  
454 Keith Stobie(Microsoft), Satish Thatte(Microsoft), Stephen Todd(IBM), Sanjiva  
455 Weerawarana(IBM), Roger Wolter(Microsoft).

456 The following individuals were members of the committee during the development of this specification:

457 Abbie Barbir(Nortel), Charlton Barreto(Adobe), Stefan Batres(Microsoft), Hamid Ben  
458 Malek(Fujitsu), Andreas Bjarlestam(Ericsson), Toufic Boubrez(Layer 7), Doug Bunting(Sun), Lloyd  
459 Burch(Novell), Steve Carter(Novell), Martin Chapman(Oracle), Dave Chappell(Sonic), Paul  
460 Cotton(Microsoft), Glen Daniels(Sonic), Doug Davis(IBM), Blake Dournaee(Intel), Jacques  
461 Durand(Fujitsu), Colleen Evans(Microsoft), Christopher Ferris(IBM), Paul Fremantle(WSO2),  
462 Robert Freund(Hitachi), Peter Furniss(Erebor), Marc Goodner(Microsoft), Alastair  
463 Green(Choreology), Mike Grogan(Sun), Ondrej Hrebicek(Microsoft), Kazunori Iwasa(Fujitsu),  
464 Chamikara Jayalath(WSO2), Lei Jin(BEA), Ian Jones(BT plc), Anish Karmarkar(Oracle), Paul  
465 Knight(Nortel), Dan Leshchiner(Tibco), Mark Little(JBoss), Lily Liu(webMethods), Matt Lovett(IBM),  
466 Ashok Malhotra(Oracle), Jonathan Marsh(Microsoft), Daniel Millwood(IBM), Jeff  
467 Mischkinsky(Oracle), Nilo Mitra(Ericsson), Peter Niblett(IBM), Duane Nickull(Adobe), Eisaku  
468 Nishiyama(Hitachi), Dave Orchard(BEA), Chouthri Palanisamy(NEC), Sanjay Patil(SAP), Gilbert  
469 Pilz(BEA), Martin Raeppele(SAP), Eric Rajkovic(Oracle), Stefan Rossmannith(SAP), Tom  
470 Rutt(Fujitsu), Rich Salz(IBM), Shivajee Samdarshi(Tibco), Vladimir Videlov(SAP), Claus von  
471 Riegen(SAP), Pete Wenzel(Sun), Steve Winkler(SAP), Ümit Yalçinalp(SAP), Nobuyuki  
472 Yamamoto(Hitachi).



## 473 Appendix B. XML Schema

474 A normative copy of the XML Schema [XML-Schema Part1, XML-Schema Part2] description for this  
475 specification may be retrieved from the following address:

476 <http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-schema-200702.xsd>

477 The following copy is provided for reference.

```
478 <?xml version="1.0" encoding="UTF-8"?>
479 <!-- Copyright(C) OASIS(R) 1993-2007. All Rights Reserved.
480 OASIS trademark, IPR and other policies apply. -->
481 <xs:schema xmlns:tns="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
482 xmlns:xs="http://www.w3.org/2001/XMLSchema"
483 targetNamespace="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
484 elementFormDefault="qualified" attributeFormDefault="unqualified">
485   <xs:element name="RMAssertion">
486     <xs:complexType>
487       <xs:sequence>
488         <xs:any namespace="##other" processContents="lax" minOccurs="0"
489 maxOccurs
490       </xs:sequence>
491       <xs:anyAttribute namespace="##any" processContents="lax"/>
492     </xs:complexType>
493   </xs:element>
494   <xs:element name="SequenceSTR">
495     <xs:complexType>
496       <xs:sequence/>
497       <xs:anyAttribute namespace="##any" processContents="lax"/>
498     </xs:complexType>
499   </xs:element>
500   <xs:element name="SequenceTransportSecurity">
501     <xs:complexType>
502       <xs:sequence/>
503       <xs:anyAttribute namespace="##any" processContents="lax"/>
504     </xs:complexType>
505   </xs:element>
506   <xs:element name="DeliveryAssurance">
507     <xs:complexType>
508       <xs:sequence>
509         <xs:any namespace="##any" processContents="lax" minOccurs="0"
510 maxOccurs="unbounded"/>
511       </xs:sequence>
512     </xs:complexType>
513   </xs:element>
514   <xs:element name="ExactlyOnce">
515     <xs:complexType>
516       <xs:sequence/>
517     </xs:complexType>
518   </xs:element>
519   <xs:element name="AtLeastOnce">
520     <xs:complexType>
521       <xs:sequence/>
522     </xs:complexType>
523   </xs:element>
524   <xs:element name="AtMostOnce">
525     <xs:complexType>
526       <xs:sequence/>
527     </xs:complexType>
528   </xs:element>
```

```
529      <xs:element name="InOrder">
530        <xs:complexType>
531          <xs:sequence/>
532        </xs:complexType>
533      </xs:element>
534    </xs:schema>
```

## 535 Appendix C. Revision History

Revision	Date	By Whom	What
wd-01.doc	2005-07-06	Ümit Yalçinalp	Initial version created based on submission by the authors.
1.0-wd-01.swx	2005-09-01	Ümit Yalçinalp	Reformatted using Open Office
1.1-wd-01.swx	2005-09-18	Ümit Yalçinalp	Applied resolution i001 Applied resolution i015/16 (doc identifier) Partial application of i017, final yyyy/mm required, changed doc URI to TBD pending yyyy/mm Deleted original copyright section
1.1-wd-01.swx	2005-10-02	Anish Karmarkar	Applied resolution of i013 + minor editorial changes + fixed resolution of i017
1.1-wd-01.swx	2005-10-04	Ümit Yalçinalp	Applied actual value for yyyy/mm. Added resolution of i009
1.1-wd-01.swx	2005-10-06	Ümit Yalçinalp	Editorial fixes suggested by Anish Updated wd draft date to October 6th
1.1-wd-01.swx	2005-10-19	Ümit Yalçinalp	Editorial change to remove .swx suffix from doc id
wd-02	2005-11-03	Gilbert Pilz	Start wd-02 by changing title page from cd-01.
wd-02	2005-11-30	Gilbert Pilz	i072 – editorial nits
wd-02	2005-11-30	Gilbert Pilz	i074 - Use of [tcShortName] in artifact locations namespaces, etc
wd-02	2005-12-01	Gilbert Pilz	Updated fix to i074 to remove trailing '/' from wsrmp namespace.
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i022
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i024
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i054
wd-02	2005-12-01	Anish Karmarkar	Applied resolution of i073
wd-2	2005-12-05	Anish Karmarkar	Applied resolution of i055
wd-2	2005-12-05	Ümit Yalçinalp	Changed fixed date in footer to current date
wd-3	2005-12-21	Doug Davis	Added i050
wd-3	2005-12-23	Ümit Yalçinalp	I057 resolution

Revision	Date	By Whom	What
wd-3	2005-12-23	Ümit Yalçınalp	Changed the ref to WS-RM to the WS-RX committee draft instead of original version Fixed Dug's email address
wd-3	2005-12-23	Ümit Yalçınalp	I060 resolution
wd-03	2005-12-27	Gilbert Pilz	Remove schema example and put it in its own artifact (wsrmp-1.1-schema-200510.xsd). Convert source file to OpenDocument format. Make line numbers all the same style.
wd-03	2005-12-28	Anish Karmarkar	Included a section link to c:\temp\wsrmp-1.1-schema-200510.xsd
wd-03	2006-01-04	Gilbert Pilz	Fixed formatting of included section.
wd-03	2006-01-05	Gilbert Pilz	Fix closing tag of normative outline for RMAssertion.
wd-04	2006-11-11	Doug Davis	Minor tweaks/typos
wd-05	2006-01-23	Gilbert Pilz	Start wd-05 by accepting all changes from wd-04
wd-06	2006-01-23	Doug Davis	Minor typos found by Marc
wd-06	2006-02-14	Doug Davis	Issue 075 resolution
wd-06	2006-02-14	Doug Davis	Issues 086, 087 resolutions
wd-06	2006-02-15	Gilbert Pilz	Issue 088; added link for namespace URI; added text describing link; added non-normative reference for RDDL 2.0
wd-06	2006-02-17	Anish Karmarkar	Removed a sentence in section 2.1 that talked about RM assertion parameters, as there aren't any.
wd-06	2006-02-17	Anish Karmarkar	Change the namespace to 200602.
wd-07	2006-02-22	Doug Davis	Accept all changes to create new WD Minor typo fixed – thanks to Paul Cotton
wd-07	2006-02-23	Doug Davis	Added missing namespace table entries - MarcG
wd-07	2006-03-08	Doug Davis	Issue 097 applied
wd-08	2006-04-11	Doug Davis	Issue 021 applied
wd-08	2006-04-24	Gilbert Pilz	Misc cleanups prior to publishing to TC.
wd-09	2006-05-29	Gilbert Pilz	Issue 117 applied
wd-10	2006-06-05	Gilbert Pilz	Accept all changes; bump WD number
wd-10	2006-06-07	Doug Davis	Applied lots of minor edits from Marc Goodner
wd-10	2006-06-13	Doug Davis	Applied a couple of minor edits

<b>Revision</b>	<b>Date</b>	<b>By Whom</b>	<b>What</b>
wd-10	2006-07-21	Doug Davis	Issues 122-124 applied
wd-10	2006-07-27	Doug Davis	Copied list of TC members from RM spec (i134)
wd-10	2006-08-04	Doug Davis	Updated old namespaces – found by PaulC
wd-10	2006-08-04	Doug Davis	Verify all [refs]
wd-10	2006-08-04	Doug Davis	Change namespace to 2006/08
cd-04	2006-08-11	Doug Davis	Issue 158 applied
cd-04	2006-08-16	Gilbert Pilz	Fix date at 08/11/2006; formatting changes for better HTML rendering.
wd-11	2006-10-25	Doug Davis	Accept all changes, update to wd11
wd-11	2006-10-26	Doug Davis	PR004 applied
wd-11	2007-01-26	Doug Davis	PR037 applied
wd-12	2007-01-31	Doug Davis	Lots of typos from MarcG Updated WD number and date
wd-12	2007-02-01	Doug Davis	PR035 (009,020 dups) applied