



---

# Glossary for the OASIS Security Assertion Markup Language (SAML) V1.1

OASIS Standard, 2 September 2003

**Document identifier:**

oasis-sstc-saml-glossary-1.1

**Location:**

[http://www.oasis-open.org/committees/documents.php?wg\\_abbrev=security](http://www.oasis-open.org/committees/documents.php?wg_abbrev=security)

**Editor:**

Eve Maler, Sun Microsystems ([eve.maler@sun.com](mailto:eve.maler@sun.com))  
Rob Philpott, RSA Security ([rphilpott@rsasecurity.com](mailto:rphilpott@rsasecurity.com))

**Contributors:**

Irving Reid, Baltimore Technologies  
Hal Lockhart, BEA Systems  
David Orchard, BEA Systems  
Zahid Ahmed, formerly of CommerceOne  
Tim Moses, Entrust  
Joe Pato, Hewlett-Packard  
Bob Blakley, IBM  
Marlena Erdos, IBM  
RL "Bob" Morgan, individual  
Marc Chanliau, Netegrity  
Prateek Mishra, Netegrity  
Darren Platt, formerly of RSA Security  
Jahan Moreh, Sigaba  
Jeff Hodges, Sun Microsystems

**Abstract:**

This specification defines terms used throughout the OASIS Security Assertion Markup Language (SAML) specifications and related documents.

**Status:**

This is an OASIS Standard document produced by the Security Services Technical Committee. It was approved by the OASIS membership on 2 September 2003.

Committee members should submit comments and potential errata to the [security-services@lists.oasis-open.org](mailto:security-services@lists.oasis-open.org) list. Others should submit them to the [security-services-comment@lists.oasis-open.org](mailto:security-services-comment@lists.oasis-open.org) list (to post, you must subscribe; to subscribe, send a message to [security-services-comment-request@lists.oasis-open.org](mailto:security-services-comment-request@lists.oasis-open.org) with "subscribe" in the body) or use

38 other OASIS-supported means of submitting comments. The committee will publish vetted errata  
39 on the Security Services TC web page (<http://www.oasis-open.org/committees/security/>).

40 For information on whether any patents have been disclosed that may be essential to  
41 implementing this specification, and any offers of patent licensing terms, please refer to the  
42 Intellectual Property Rights web page for the Security Services TC ([http://www.oasis-  
43 open.org/committees/security/ipr.php](http://www.oasis-open.org/committees/security/ipr.php)).

44

---

45 **Table of Contents**

46 1 Glossary ..... 4  
47 2 References ..... 11  
48 Appendix A. Acknowledgments ..... 12  
49 Appendix B. Notices ..... 13  
50

---

# 1 Glossary

52 This normative document defines terms used throughout the OASIS Security Assertion Markup Language  
53 (SAML) specifications and related documents.

54 Some definitions are derived directly from external sources (referenced in an appendix), some definitions  
55 based on external sources have been substantively modified to fit the SAML context, and some are newly  
56 developed for SAML. Please refer to the external sources for definitions of terms not explicitly defined  
57 here.

58 Some definitions have multiple senses provided. They are denoted by (a), (b), and so on. References to  
59 terms defined elsewhere in this glossary are italicized.

60 Following are the defined terms used in the SAML specifications and related documents.

Term	Definition
Access	To interact with a <i>system entity</i> in order to manipulate, use, gain knowledge of, and/or obtain a representation of some or all of a system entity's <i>resources</i> . [RFC2828]
Access Control	Protection of <i>resources</i> against unauthorized access; a process by which use of resources is regulated according to a security policy and is permitted by only authorized system entities according to that policy. [RFC2828]
Access Control Information	Any information used for access control purposes, including contextual information [X.812]. Contextual information might include source IP address, encryption strength, the type of operation being requested, time of day, etc. Portions of access control information may be specific to the request itself, some may be associated with the connection via which the request is transmitted, and others (for example, time of day) may be "environmental". [RFC2829]
Access Rights	A description of the type of authorized interactions a <i>subject</i> can have with a <i>resource</i> . Examples include read, write, execute, add, modify, and delete. [Taxonomy]
Active Role	A role that a <i>system entity</i> has donned when performing some operation, for example accessing a <i>resource</i> .
Administrative Domain	An environment or context that is defined by some combination of one or more administrative policies, Internet Domain Name registrations, civil legal entities (for example, individuals, corporations, or other formally organized entities), plus a collection of hosts, network devices and the interconnecting networks (and possibly other traits), plus (often various) network services and applications running upon them. An administrative domain may contain or define one or more security domains. An administrative domain may encompass a single site or multiple sites. The traits defining an administrative domain may, and in many cases will, evolve over time. Administrative domains may interact and enter into agreements for providing and/or consuming services across administrative domain boundaries.

Term	Definition
Administrator	A person who installs or maintains a system (for example, a SAML-based security system) or who uses it to manage <i>system entities</i> , users, and/or content (as opposed to application purposes; see also <i>End User</i> ). An administrator is typically affiliated with a particular <i>administrative domain</i> and may be affiliated with more than one administrative domain.
Anonymity	The quality or state of being anonymous, which is the condition of having a name or identity that is unknown or concealed. <b>[RFC2828]</b>
Assertion	A piece of data produced by a <i>SAML authority</i> regarding either an act of authentication performed on a <i>subject</i> , attribute information about the subject, or authorization permissions applying to the subject with respect to a specified <i>resource</i> .
Asserting Party	Formally, the <i>administrative domain</i> that hosts one or more <i>SAML authorities</i> . Informally, an instance of a <i>SAML authority</i> .
Attribute	A distinct characteristic of an object (in SAML, of a <i>subject</i> ). An object's attributes are said to describe it. Attributes are often specified in terms of physical traits, such as size, shape, weight, and color, etc., for real-world objects. Objects in cyberspace might have attributes describing size, type of encoding, network address, and so on. Which attributes of an object are salient is decided by the beholder. See also <i>XML attribute</i> .
Attribute Authority	A <i>system entity</i> that produces <i>attribute assertions</i> . <b>[SAMLAgree]</b>
Attribute Assertion	An <i>assertion</i> that conveys information about <i>attributes</i> of a <i>subject</i> .
Authentication	To confirm a <i>system entity's</i> asserted <i>principal identity</i> with a specified, or understood, level of confidence. <b>[CyberTrust] [SAMLAgree]</b>
Authentication Assertion	An <i>assertion</i> that conveys information about a successful act of <i>authentication</i> that took place for a <i>subject</i> .
Authentication Authority	A <i>system entity</i> that produces <i>authentication assertions</i> . <b>[SAMLAgree]</b>
Authorization	The process of determining, by evaluating applicable <i>access control information</i> , whether a <i>subject</i> is allowed to have the specified types of <i>access</i> to a particular <i>resource</i> . Usually, authorization is in the context of authentication. Once a subject is authenticated, it may be authorized to perform different types of access. <b>[Taxonomy]</b>
Authorization Decision	The result of an act of authorization. The result may be negative, that is, it may indicate that the <i>subject</i> is not allowed any access to the <i>resource</i> .
Authorization Decision Assertion	An <i>assertion</i> that conveys information about an <i>authorization decision</i> .
Binding, Protocol Binding	An instance of mapping SAML request-response message exchanges into a specific protocol. Each binding is given a name in the pattern "SAML xxx binding".
Credentials	Data that is transferred to establish a claimed principal identity. <b>[X.800] [SAMLAgree]</b>

Term	Definition
End User	A natural person who makes use of resources for application purposes (as opposed to system management purposes; see <i>Administrator, User</i> ).
Identifier	A representation (for example, a string) mapped to a <i>system entity</i> that uniquely refers to it.
Initial SOAP Sender	The SOAP sender that originates a SOAP message at the starting point of a SOAP message path. <b>[WSGloss]</b>
Login, Logon, Sign-On	The process whereby a <i>user</i> presents <i>credentials</i> to an <i>authentication authority</i> , establishes a <i>simple session</i> , and optionally establishes a <i>rich session</i> .
Logout, Logoff, Sign-Off	The process whereby a <i>user</i> signifies desire to terminate a <i>simple session</i> or <i>rich session</i> .
Markup Language	A set of <i>XML elements</i> and <i>XML attributes</i> to be applied to the structure of an XML document for a specific purpose. A markup language is typically defined by means of a set of <i>XML schemas</i> and accompanying documentation. For example, the <i>Security Assertion Markup Language (SAML)</i> is defined by two schemas and a set of normative SAML specification text.
Party	Informally, one or more <i>principals</i> participating in some process or communication, such as receiving an <i>assertion</i> or accessing a <i>resource</i> .
Policy Decision Point (PDP)	A <i>system entity</i> that makes <i>authorization decisions</i> for itself or for other system entities that request such decisions. <b>[PolicyTerm]</b> For example, a SAML PDP consumes authorization decision requests, and produces <i>authorization decision assertions</i> in response. A PDP is an "authorization decision authority".
Policy Enforcement Point (PEP)	A <i>system entity</i> that requests and subsequently enforces <i>authorization decisions</i> . <b>[PolicyTerm]</b> For example, a SAML PEP sends <i>authorization decision</i> requests to a PDP, and consumes the <i>authorization decision assertions</i> sent in response.
Principal	A <i>system entity</i> whose identity can be authenticated. <b>[X.811]</b>
Principal Identity	A representation of a principal's identity, typically an <i>identifier</i> .
Profile	A set of rules describing how to embed <i>assertions</i> into and extract them from a framework or protocol. Each profile is given a name in the pattern "xxx profile of SAML".
Proxy	<ul style="list-style-type: none"> <li>a) An entity authorized to act for another.</li> <li>b) Authority or power to act for another.</li> <li>c) A document giving such authority. <b>[Merriam]</b></li> </ul>
Proxy Server	A computer process that relays a protocol between client and server computer systems, by appearing to the client to be the server and appearing to the server to be the client. <b>[RFC2828]</b>
Pull	To actively request information from a <i>system entity</i> .

Term	Definition
Push	To provide information to a <i>system entity</i> that did not actively request it.
Relying Party	A <i>system entity</i> that decides to take an action based on information from another system entity. For example, a SAML relying party depends on receiving <i>assertions</i> from an <i>asserting party</i> (a <i>SAML authority</i> ) about a <i>subject</i> .
Requester, SAML Requester	A <i>system entity</i> that utilizes the SAML protocol to request services from another system entity (a <i>SAML authority</i> , a <i>responder</i> ). The term “client” for this notion is not used because many system entities simultaneously or serially act as both clients and servers. In cases where the SOAP binding for SAML is being used, the SAML requester is architecturally distinct from the <i>initial SOAP sender</i> .
Resource	<ul style="list-style-type: none"> <li>a) Data contained in an information system (for example, in the form of files, information in memory, etc).</li> <li>b) A service provided by a system.</li> <li>c) An item of system equipment (in other words, a system component such as hardware, firmware, software, or documentation).</li> <li>d) A facility that houses system operations and equipment. <b>[RFC2828]</b></li> </ul> <p>SAML uses “resource” in the first two senses, and refers to resources by means of <i>URI references</i>.</p>
Responder, SAML Responder	A <i>system entity</i> (a <i>SAML authority</i> ) that utilizes the SAML protocol to respond to a request for services from another system entity (a <i>requester</i> ). The term “server” for this notion is not used because many system entities simultaneously or serially act as both clients and servers. In cases where the SOAP binding for SAML is being used, the SAML responder is architecturally distinct from the <i>ultimate SOAP receiver</i> .
Role	Dictionaries define a role as “a character or part played by a performer” or “a function or position.” Principals don various types of roles serially and/or simultaneously, for example, active roles and passive roles. The notion of an Administrator is often an example of a role.
SAML Authority	An abstract <i>system entity</i> in the SAML domain model that issues <i>assertions</i> . See also <i>attribute authority</i> , <i>authentication authority</i> , and <i>policy decision point (PDP)</i> .
Security	A collection of safeguards that ensure the confidentiality of information, protect the systems or networks used to process it, and control access to them. Security typically encompasses the concepts of secrecy, confidentiality, integrity, and availability. It is intended to ensure that a system resists potentially correlated attacks. <b>[CyberTrust]</b>

Term	Definition
Security Architecture	A plan and set of principles for an <i>administrative domain</i> and its <i>security domains</i> that describe the security services that a system is required to provide to meet the needs of its users, the system elements required to implement the services, and the performance levels required in the elements to deal with the threat environment. A complete security architecture for a system addresses administrative security, communication security, computer security, emanations security, personnel security, and physical security, and prescribes security policies for each. A complete security architecture needs to deal with both intentional, intelligent threats and accidental threats. A security architecture should explicitly evolve over time as an integral part of its administrative domain's evolution. <b>[RFC2828]</b>
Security Assertion	An <i>assertion</i> that is scrutinized in the context of a security architecture.
Security Assertion Markup Language, SAML	The set of specifications describing <i>security assertions</i> that are encoded in <i>XML</i> , <i>profiles</i> for attaching the assertions to various protocols and frameworks, the request/response protocol used to obtain the assertions, and <i>bindings</i> of this protocol to various transfer protocols (for example, SOAP and HTTP).
Security Domain	An environment or context that is defined by security models and a <i>security architecture</i> , including a set of <i>resources</i> and set of <i>system entities</i> that are authorized to access the resources. One or more security domains may reside in a single <i>administrative domain</i> . The traits defining a given security domain typically evolve over time. <b>[Taxonomy]</b>
Security Policy	A set of rules and practices that specify or regulate how a system or organization provides security services to protect <i>resources</i> . Security policies are components of <i>security architectures</i> . Significant portions of security policies are implemented via <i>security services</i> , using <i>security policy expressions</i> . <b>[RFC2828] [Taxonomy]</b>
Security Policy Expression	A mapping of <i>principal identities</i> and/or <i>attributes</i> thereof with allowable actions. Security policy expressions are often essentially access control lists. <b>[Taxonomy]</b>
Security Service	A processing or communication service that is provided by a system to give a specific kind of protection to resources, where said resources may reside with said system or reside with other systems, for example, an authentication service or a PKI-based document attribution and authentication service. A security service is a superset of AAA services. Security services typically implement portions of <i>security policies</i> and are implemented via security mechanisms. <b>[RFC2828] [Taxonomy]</b>
Session	A lasting interaction between system entities, often involving a user, typified by the maintenance of some state of the interaction for the duration of the interaction.
Site	An informal term for an <i>administrative domain</i> in geographical or DNS name sense. It may refer to a particular geographical or topological portion of an administrative domain, or it may encompass multiple administrative domains, as may be the case at an ASP site.



Term	Definition
SSO Assertion, Single Sign-On Assertion	An assertion with conditions embedded that explicitly define its lifetime, and that also contains one or more statements about the authentication of a subject. Additional information about the subject, such as attributes, may also be included in the assertion. <b>[SAMLBind]</b>
Subject	A <i>principal</i> in the context of a <i>security domain</i> . SAML assertions make declarations about subjects.
System Entity	An active element of a computer/network system. For example, an automated process or set of processes, a subsystem, a person or group of persons that incorporates a distinct set of functionality. <b>[RFC2828]</b> <b>[SAMLAgree]</b>
Time-Out	A period of time after which some condition becomes true if some event has not occurred. For example, a <i>session</i> that is terminated because its state has been inactive for a specified period of time is said to “time out”.
Ultimate SOAP Receiver	The SOAP receiver that is a final destination of a SOAP message. It is responsible for processing the contents of the SOAP body and any SOAP header blocks targeted at it. In some circumstances, a SOAP message might not reach an ultimate SOAP receiver, for example because of a problem at a SOAP intermediary. An ultimate SOAP receiver cannot also be a SOAP intermediary for the same SOAP message. <b>[WSGloss]</b>
User	A natural person who makes use of a system and its resources for any purpose <b>[SAMLAgree]</b>
Uniform Resource Identifier (URI)	A compact string of characters for identifying an abstract or physical <i>resource</i> . <b>[RFC2396]</b> URIs are the universal addressing mechanism for resources on the World Wide Web. Uniform Resource Locators (URLs) are a subset of URIs that use an addressing scheme tied to the resource’s primary access mechanism, for example, their network “location”.
URI Reference	A <i>URI</i> that is allowed to have an appended number sign (#) and fragment identifier. <b>[RFC2396]</b> Fragment identifiers address particular locations or regions within the identified resource.
XML	Extensible Markup Language, abbreviated XML, describes a class of data objects called XML documents and partially describes the behavior of computer programs which process them. <b>[XML]</b>
XML Attribute	An XML data structure that is embedded in the start-tag of an XML element and that has a name and a value. For example, the italicized portion below is an instance of an XML attribute: <pre data-bbox="643 1604 1386 1629" style="background-color: #f0f0f0; padding: 5px; text-align: center;">&lt;Address AddressID="A12345"&gt;...&lt;/Address&gt;</pre> See also <i>attribute</i> .

Term	Definition
XML Element	<p>An XML data structure that is hierarchically arranged among other such structures in an XML document and is indicated by either a start-tag and end-tag or an empty tag. For example:</p> <pre data-bbox="643 365 1386 611"> &lt;Address AddressID="A12345"&gt;   &lt;Street&gt;105 Main Street&lt;/Street&gt;   &lt;City&gt;Springfield&lt;/City&gt;   &lt;StateOrProvince&gt;     &lt;Full&gt;Massachusetts&lt;/Full&gt;     &lt;Abbrev&gt;MA&lt;/Abbrev&gt;   &lt;/StateOrProvince&gt;   &lt;Post Code="567890"/&gt; &lt;/Address&gt; </pre>
XML Namespace	<p>A collection of names, identified by a <i>URI reference</i>, which are used in XML documents as element types and attribute names. An XML namespace is often associated with an <i>XML schema</i>. For example, SAML defines two schemas, and each has a unique XML namespace.</p>
XML Schema	<p>The format developed by the World Wide Web Consortium (W3C) for describing rules for a <i>markup language</i> to be used in a set of XML documents. In the lowercase, a "schema" or "XML schema" is an individual instance of this format. For example, SAML defines two schemas, one containing the rules for XML documents that encode security assertions and one containing the rules for XML documents that encode request/response protocol messages. Schemas define not only XML elements and XML attributes, but also datatypes that apply to these constructs.</p>

---

## 2 References

- 61
- 62     **[CyberTrust]**     *Trust in Cyberspace*. Committee on Information Systems Trustworthiness, Fred  
63     B. Schneider, editor. National Research Council, ISBN 0-309-06558-5, 1999.  
64     Online copy and ordering information available at  
65     <http://www.nap.edu/readingroom/books/trust/>. Glossary:  
66     <http://www.nap.edu/readingroom/books/trust/trustapk.htm>.
- 67     **[Merriam]**         *Merriam-Webster Collegiate Dictionary*. CDROM Version 2.5, 2000. An online  
68     version is available at <http://www.m-w.com>.
- 69     **[PolicyTerm]**     *Terminology for Policy-Based Management*. A. Westerinen et al. IETF RFC  
70     3198. Available at <http://www.ietf.org/rfc/rfc3198.txt>.
- 71     **[RFC2396]**         *Uniform Resource Identifiers (URI): Generic Syntax*. T. Berners-Lee, R. Fielding,  
72     L. Masinter. IETF RFC 2396, 1998. Available at <http://www.ietf.org/rfc/rfc2396.txt>.
- 73     **[RFC2828]**         *Internet Security Glossary*. Robert W. Shirey, IETF RFC 2828, May 2000.  
74     Available at <http://www.ietf.org/rfc/rfc2828.txt>.
- 75     **[RFC2829]**         *Authentication Methods for LDAP*. M. Wahl, H. Alvestrand, J. Hodges, R.  
76     Morgan. IETF RFC 2829, May 2000. Available at [http://www.rfc-](http://www.rfc-editor.org/rfc/rfc2829.txt)  
77     [editor.org/rfc/rfc2829.txt](http://www.rfc-editor.org/rfc/rfc2829.txt).
- 78     **[SAMLAgree]**        *OASIS Security Services TC Use Case and Requirements Conference Call*  
79     *Consensus*. Consensus on the wording for this item occurred during one or more  
80     conference calls of the SAML Use Cases and Requirements subcommittee.  
81     Meeting minutes are available at [http://lists.oasis-open.org/archives/security-](http://lists.oasis-open.org/archives/security-use/)  
82     [use/](http://lists.oasis-open.org/archives/security-use/).
- 83     **[SAMLBind]**        E. Maler et al. *Bindings and Profiles for the OASIS Security Assertion Markup*  
84     *Language (SAML)*. OASIS, September 2003. Document ID oasis-sstc-saml-  
85     bindings-1.1. <http://www.oasis-open.org/committees/security/>.
- 86     **[Taxonomy]**        *Security Taxonomy and Glossary*. Lynn Wheler, ongoing. Availabe at  
87     <http://www.garlic.com/~lynn/secure.htm>. See <http://www.garlic.com/~lynn/> for the  
88     list of sources.
- 89     **[X.800]**            *Information processing systems – Open Systems Interconnection – Basic*  
90     *Reference Model – Part 2: Security Architecture*. ISO 7498-2:1989, ITU-T  
91     Recommendation X.800 (1991). Available at [http://www.itu.int/itudoc/itu-](http://www.itu.int/itudoc/itu-t/rec/x/x500up/x800.html)  
92     [t/rec/x/x500up/x800.html](http://www.itu.int/itudoc/itu-t/rec/x/x500up/x800.html).
- 93     **[X.811]**            *Security Frameworks for Open Systems: Authentication Framework*. ITU-T  
94     Recommendation X.811 (1995 E), ISO/IEC 10181-2:1996(E). Available at  
95     <http://www.itu.int/itudoc/itu-t/rec/x/x500up/x811.html>.
- 96     **[X.812]**            *Security frameworks for open systems: Access control framework*. ITU-T  
97     Recommendation X.812 (1995 E), ISO/IEC 10181-3:1996(E). Available at  
98     <http://www.itu.int/itudoc/itu-t/rec/x/x500up/x812.html>.
- 99     **[XML]**             *Extensible Markup Language (XML) 1.0 (Second Edition)*. W3C  
100     Recommendation, October 2000. Available at [http://www.w3.org/TR/2000/REC-](http://www.w3.org/TR/2000/REC-xml-20001006)  
101     [xml-20001006](http://www.w3.org/TR/2000/REC-xml-20001006).
- 102     **[WSGloss]**         *Web Services Glossary*, W3C Working Draft, November 2002. Available at  
103     <http://www.w3.org/TR/ws-gloss/>.

---

## 104 **Appendix A. Acknowledgments**

105 The editors would like to acknowledge the contributions of the OASIS Security Services Technical  
106 Committee, whose voting members at the time of publication were:

- 107 • Frank Siebenlist, Argonne National Laboratory
- 108 • Irving Reid, Baltimore Technologies
- 109 • Hal Lockhart, BEA Systems
- 110 • Steven Lewis, Booz Allen Hamilton
- 111 • John Hughes, Entegriety
- 112 • Carlisle Adams, Entrust
- 113 • Jason Rouault, Hewlett-Packard
- 114 • Maryann Hondo, IBM
- 115 • Anthony Nadalin, IBM
- 116 • Scott Cantor, individual
- 117 • RL “Bob” Morgan, individual
- 118 • Trevor Perrin, individual
- 119 • Padraig Moloney, NASA
- 120 • Prateek Mishra, Netegrity (co-chair)
- 121 • Frederick Hirsch, Nokia
- 122 • Senthil Sengodan, Nokia
- 123 • Timo Skytta, Nokia
- 124 • Charles Knouse, Oblix
- 125 • Steve Anderson, OpenNetwork
- 126 • Simon Godik, Overxeer
- 127 • Rob Philpott, RSA Security (co-chair)
- 128 • Dipak Chopra, SAP
- 129 • Jahan Moreh, Sigaba
- 130 • Bhavna Bhatnagar, Sun Microsystems
- 131 • Jeff Hodges, Sun Microsystems
- 132 • Eve Maler, Sun Microsystems (coordinating editor)
- 133 • Emily Xu, Sun Microsystems
- 134 • Phillip Hallam-Baker, VeriSign

135

---

## Appendix B. Notices

136  
137  
138  
139  
140  
141  
142  
143

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS's procedures with respect to rights in OASIS specifications can be found at the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification, can be obtained from the OASIS Executive Director.

144  
145  
146

OASIS invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to implement this specification. Please address the information to the OASIS Executive Director.

147

**Copyright © OASIS Open 2003. All Rights Reserved.**

148  
149  
150  
151  
152  
153  
154  
155

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to OASIS, except as needed for the purpose of developing OASIS specifications, in which case the procedures for copyrights defined in the OASIS Intellectual Property Rights document must be followed, or as required to translate it into languages other than English.

156  
157

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

158  
159  
160  
161

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.